

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

NONE

DIAGRAM
T32S, R3W, W.M.
C 1/4 S 22
RLS 536 1974

Description of corner evidence found:

NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Glenn S. Baughman
OREGON
JULY 14 1961
GLENN S. BAUGHMAN
536

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 36-inch long, 2 1/2 inch galvanized iron pipe 32 inches in the ground, in a mound of stones, with a 4-inch brass cap marked:

Bearing trees:

a white fir, 10 inches diameter bears
S 56° W 9.4 feet scribed C 1/4 S 22 (BT)
with brass washer stamped RLS 536

T32S R3W
C 1/4 S22
RLS 536 1974

a madrona, 13 inches diameter bears N 48° E
10.6 feet scribed C 1/4 S 22 (BT) with a
brass washer stamped RLS 536

From Book #6, page 13, Tiller Land Survey #13 - Contract #004346N.

Office of County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of; 19....., at..... o'clockm., (signed)
..... by
(COUNTY OFFICIAL) (DEPUTY)

FILED
RECEIVED *Seals*
M 44-69
AUG 8 1974

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE