

3-28-74

$\frac{5}{8} | \frac{4}{9}$

T 325 RGW

(RENEWAL #101)

FD:

BRASS CAP SET BY COUNTY SURVEYOR
IN 1967 OUT OF THE GROUND.

BRASS CAP MARKED:

COUNTY SURVEYOR'S OFFICE
T 325 RGW

$\frac{55}{58} | \frac{54}{59}$

1967

I ADD THE MARKINGS "1974" TO THE
BRASS CAP AND SET IT AT THE RECORD
BEARING AND DISTANCE FROM AN
ORIGINAL 36" NOW 46" PINE SNAG
BT WITH SCRIBING "2 S 5 T" VISIBLE
ON PREVIOUSLY OPENED BLAZE.

NOTE:

CORNER RENEWAL #101 CALLS
FOR BEARING TO THIS NW ORIGINAL

#135 ✓

PINE BT TO BE $N48^{\circ}W$. THE ORIGINAL SURVEY NOTES CALL FOR $N40^{\circ}W$. I SET THE BRASS CAP AT THE ORIGINAL BEARING AND DISTANCE OF $N40^{\circ}W$ 23 $\frac{1}{2}$ -FT. FROM THIS PINE BT.

BEARING TREES:

36" NOW 46" PINESNAG BEARS $N40^{\circ}W$ 23 $\frac{1}{2}$ -FT, WITH MARKS SHOWING AS NOTED ABOVE

5" NOW 6" MADRONE BEARS $S74^{\circ}W$ 20 $\frac{0}{2}$ -FT ($S74^{\circ}W$ 24 $\frac{2}{2}$ -FT REN.#101) WITH SCRIBING "S B BT" VISIBLE.

6" NOW 7" CHINQUAPIN BEARS $S59\frac{1}{2}^{\circ}E$ 14 $\frac{2}{2}$ -FT ($S52\frac{1}{2}^{\circ}E$ 12 $\frac{2}{2}$ -FT. REN.#101) WITH SCRIBING "T323 R6W S9 CS BT" VISIBLE.

16" NOW 18" D. FIR BEARS $N62^{\circ}E$ 23 $\frac{6}{2}$ -FT ($N58^{\circ}E$ 21 $\frac{8}{2}$ -FT (GN.#101) WITH SCRIBING "26W S4 BT" VISIBLE

NEW BEARING TREE:

22" D. FIR BEARS N 29 1/2° W 62 3/4 FT
SCRIBED "T 325 R 6W S 5 CS BT"

3-28-74

Larry Langley
PETER L. EAGLE

OK
JHL