

8-29-74

$\frac{6}{7} \mid \frac{5}{8}$

T295 R1E

FD:

AN ORIG 24' HEMLOCK, NOW A 26" STUMP, ROTTEN. WE OPEN AND FIND GOOD SCRIBING "295 R1E S6 BT".

THERE IS NO TRACE OF THE THREE REMAINING ORIGINAL BEARING TREES OR THE ORIGINAL CORNER MONUMENT.

AT THE TRUE CORNER POINT AS DETERMINED FROM THE ONLY REMAINING ORIG. B.T., A 26' HEMLOCK STUMP, BEARING N82°W 43.6 FT., WE SET A BRASS CAP MARKED;

COUNTY SURVEYOR'S OFFICE

T295

$\frac{56}{57} \mid \frac{55}{58}$

R1E

1974

TO OBT NW 26" HEMLOCK STUMP

ROTCW

41° @ 19½° .9426

386

+ 5°

436

NEW NE BT 6" G. FIR

N 66° E 356 LVL

"T295 RIE 55 CS BT"

NEW SE BT 5" G. FIR

S 23° E

45 5 @ 9° .98769 442

"58 CS BT"

RP 16 @ 32

FROM WHICH WE MARK THE FOLLOWING
BEARING TREES;

A 6" GRAND FIR BEARS N 66° E
35 6 FT., SCRIBED "T29S RIE
S 5 CS BT"

A 5" GRAND FIR BEARS S 23° E
44 2 FT., SCRIBED "S 8 CS BT"

THERE ARE NO OTHER SUITABLE TREES
IN THE VICINITY.

THIS CORNER LIES AT THE BOTTOM
OF THE CUTBANK AND ALONG THE
WESTERLY EDGE OF AN ABANDONED
LOGGING ROAD. IT IS ALSO
SITUATED IN AN OLD LOGGING
UNIT.

8-29-74

Larry Jangles
PETE EARLE