

10-16-74

| | |
|----|----|
| 26 | 25 |
| 35 | 36 |

T29S R1E

FO:

A STONE, 16" X 12" X 6" (REC. 18" X 15" X 6")
FIRMLY SET AND MARKED WITH AN "+" CHISELED
ON TOP AND ONE NOTCH OF THE SOUTH AND EAST
EDGES, FROM WHICH:

AN ORIG 15" NOW 25" INCENSE CEDAR BEARS
N 67° E 21² FT., ALIVE AND WELL-HEALED

AN ORIG. 12" D. FIR, NOW A 14" SNAG BEARS
S 53° W 15[±] FT., WELL-HEALED.

AN ORIG 6" NOW 10" MADRONE BEARS N 13° W
15² FT., ALIVE WITH SCRIBING "T2 R1E S2
BT" SHOWING ON UNHEALED AND BADLY
ROTING FACE.

THERE IS NO EVIDENCE REMAINING OF THE
ORIGINAL SE BEARING TREE.

#88 ✓

U.S. File No. 57/P-13 PAGE 1 C

23⁴@15° .96593

22⁶

NEW SE BT || "T. CEDAR

13⁷-LVL

546¹/₂°E

T295 R1E S36 CSBT

12" D. Fir

573¹/₂°W

17²-LVL

T295 R1E S35 CSBT

10" D. Fir

N9°E

21³@15° .96593

20⁶

T295 R1E S25 CSBT

AT TAG CORNER POINT, WE SET A 1" X 30" IRON
PIPE WITH A BRASS CAP ATTACHED, MARKED:

COUNTY SURVEYOR'S OFFICE

T295

| | |
|-----|-----|
| S26 | S25 |
| S35 | S36 |

R1E

1974

WE PLACE THE ORIGINAL STONE ALONGSIDE
THE BRASS CAP AND MARK THE FOLLOWING
BEARING TREES:

A 12" D. FIR BEARS S $73\frac{1}{2}^{\circ}$ W 17² FT.,
SCRIBED "T295 R1E S35 CSBT"

A 10" D. FIR BEARS N 9° E 20⁵ FT.,
SCRIBED "T295 R1E S25 CSBT".

AN 11" INCENSE CEDAR BEARS S $46\frac{1}{2}^{\circ}$ E
13² FT., SCRIBED "T295 R1E S36 CSBT".

COMPASS DECLINATION SETTING: 20° EAST.

10-16-74

Gary L. Langley
PETER L. EARLE