

1-16-75

$\frac{1}{4} \frac{10}{15}$ T215 RTW

(SEE REN. # 83)

FD:

"T" IRON SET BY HAINES IN 1965,
FIRMLY SET FROM WHICH THE ONLY REMAIN-
ING BEARING TREE MARKED BY HAINES,
AN 11" HEMLOCK, NOW A STUMP BEARS
S 72° W 11 $\frac{3}{4}$ FT., WITH SCRIBING "1/45 BT"
VISIBLE ON UNHEALED BLAZES.

HAINES' NE BT HAS BEEN COMPLETELY REMOVED.

AT THE CORNER POINT WE SET A 1" X 30"
IRON PIPE WITH BRASS CAP ATTACHED,

MARKED:

COUNTY SURVEYORS OFFICE

T215

$\frac{1}{4} \frac{510}{515}$

RTW

1975

WE DEPOSIT THE "T" IRON ALONGSIDE THE
BRASS CAP AND MARK THE FOLLOWING BT'S:

#102 ✓

C. S. File No. 57117-B

PAGE 1 ^C

DIETZBEN NO. 385-6

10 ~~5~~" HEMLOCK

59 ~~4~~ @ 22° .9272

55'

S 66° W

$\frac{1}{4}$ S 13 CS BT

~~11" HEMLOCK~~

41 ~~2~~ @ 28° .8829

37°

N 9° W

$\frac{1}{4}$ S 10 CS BT

A 10" HEMLOCK BEARS S 66° W 55⁺ FT.,
SCRIBED " 1/4 S 15 CS BT "

AN 11" HEMLOCK BEARS N 9° W 37° FT.,
SCRIBED " 1/4 S 10 CS BT "

THIS CORNER IS LOCATED IN A CLEARCUT UNIT
NEAR THE TOP OF A SMALL RIDGE SLOPING
STEEPLY TO THE NORTHEAST.

COMPASS DECLINATION SETTING: 20° EAST.

1-16-75

Larry L. Langley
JOHN E. NORDLING

OK
[Signature]