

RENEWAL 6-19-75

T27S R1W

S 29 S 28

S 32 S 33

FOUND

12" X 10" X 8" BASALT STONE ON
SURFACE OF GROUND. 4 NOTCHES
ON EAST EDGE & 1 NOTCH ON
SOUTH EDGE. FROM WHICH
A 63 INCH DIA. FIR STUMP
BEARS N 78° E 8½ FEET.

STUMP CUT BELOW NORMAL
NOTCH HEIGHT. ORIGINAL
NOTES CALL FOR 60 INCH FIR
ON LINE BETWEEN SECTIONS
28 AND 33 A DISTANCE OF
3³ FEET EAST OF CORNER.

NO BEARING TREES FOUND.

ORIGINAL CALL ON SOUTH
LINE TO SPRING CHECKED,
NO TRACE OF CABIN, AREA
CAT LOGGED & BURNED.

#131
C

C. S. FILE No. 57/30-11

②

RENEWAL

33 FT. WEST OF LINE TREE, I
SET IRON PIPE 2 1/2 FEET
IN LENGTH 1 1/2 INCH IN DIA.
WITH 2 1/2 INCH BRASS CAP.
STAMPED

"COUNTY SURVEYORS OFFICE"

"T27S R1W

S 29	S 28
S 32	S 33

1975"

BEARING OBJECTS

(NO TREES AVAILABLE)

5/8" IRON ROD WITH ALUMINUM
CAP 1 1/2 INCH DIAMETER
CAP CENTER PUNCHED & STAMPED

"DOUGLAS CO. SURVEYOR

B.O. NO. 1"

SET IN ORIGINAL LINE

T275 RLW

29 / 28
32 / 33

②

TREE ^{STUMP} BEARS N 75° E 3⁸ FT.

5"
8 IRON ROD WITH ALUMINUM CAP
1 1/2 INCHES IN DIAMETER SET
IN 48 INCH DIA. CEDAR STUMP
BEARS S 25 1/2° E 64 ± FEET.

CAP CENTER PUNCHED & STAMPED

"DOUGLAS CO. SURVEYOR"

B.O. NO. 2

5"
8 IRON ROD WITH ALUMINUM

CAP 1 1/2 INCHES IN DIAMETER

CAP CENTER PUNCHED & STAMPED

"DOUGLAS CO. SURVEYOR"

B.O. NO. 3

BEARS S 75° W 22² FEET.

12" X 10" X 8" STONE (BASALT)

WITH 4 NOTCHES ON EAST

EDGE & ONE NOTCH ON SOUTH

EDGE, LYING ON GROUND SURFACE

BEARS S 59° W 5⁸ FEET

DIETZGEN NO. 385-6

C. S. File No. 57/30-11

④

5/8 INCH IRON ROD WITH
ALUMINIUM CAP 1/2 INCH
IN DIAMETER SET IN A
30 INCH DIAMETER FIR
STUMP. CAP CENTER
PUNCHED & STAMPED

"DOUGLAS CO. SURVEYOR"
B.O. NO. 4

BEARS N 58 1/2° W 70 8 FEET

6-19-75

L. E. MONTREAN

P. L. EARLE

A. V. CANGLE

OK
JHL