

6-23-75

T 285 R 1 W

$$\begin{array}{r} 4/3 \\ 9/10 \end{array}$$
FD:

A STONE, 12" X 10" X 5" (REC. 15" X 10" X 5"), BURIED  
IN DEBRIS, MARKED WITH 5 NOTCHES ON  
THE SOUTH EDGE AND 4 NOTCHES ON THE  
EAST EDGE (REC. 3 NOTCHES),

FROM WHICH:

AN ORIG. 12" NOW 15" RED CEDAR BEARS  
N 41° E 14<sup>3</sup>/<sub>4</sub> FT., SCRIBE MARKS VISIBLE  
THROUGH SMALL UNHEALED OPENING.

AN ORIG. 14" NOW 19" D. FIR BEARS S 45° E  
21<sup>1</sup>/<sub>2</sub> FT., (REC. S 50° E 21<sup>1</sup>/<sub>2</sub> FT.), ALIVE  
AND WELL-HEALED.

AN ORIG. 12" NOW 13" D. FIR BEARS S 48° W  
25<sup>1</sup>/<sub>2</sub> FT., ALIVE AND WELL-HEALED.

AND AN ORIG. 12" NOW 18" D. FIR BEARS N 38° W  
26<sup>1</sup>/<sub>4</sub> FT., ALIVE AND WELL-HEALED.

#281c

C. S. File No. 57/30-14-1

PAGE 1

AT THE CORNER POINT WE SET A 1" X 30" I. PIPE  
WITH BRASS CAP ATTACHED, MARKED:

COUNTY SURVEYORS OFFICE

T 28 S

S 4	S 3
S 9	S 10

R 1 W

1975

WE PLACE THE ORIGINAL CORNER STONE  
ALONGSIDE THE BRASS CAP.

COMPASS DECLINATION SETTING: 20° EAST

6-23-75

*Gary L. Langlet*

GREG. E. QUIBELL

*OK*  
*Jed*

DIETZGEN NO. 3855-R