

8-4-75

T245
 $\frac{1}{4}$ $\frac{31}{6}$ RSW

T255

CORNER LOCATION DETERMINED BY SINGLE PROPORTIONATE MEASUREMENT.

AT THE CORNER POINT, WE SET A 1" X 24" I. PIPE, FLUSH IN THE GROUND, WITH BRASS CAP ATTACHED, MARKED:

DOUGLAS CO. SURVEYOR

T245

$\frac{1}{4}$ $\frac{31}{6}$ RSW

T255

1975

AND MARK THE FOLLOWING BEARING TREES:

A 36" FORKED W. OAK BEARS N 25° E
41 6 FT., SCRIBED " $\frac{1}{4}$ S 31 CS BT "

ON A DOUBLE BLAZE,

93 T245
127 T255
S. File No. 57/34-11

(OVER)

PAGE 1

DITZGEN N.D. 389-5

AND A 21" W. OAK BEARS S 17° W
164⁸ FT., SCRIBED "1/4 S 6 CS BT"
ON A DOUBLE BLAZE.

NOTE:

THIS CORNER IS LOCATED APPROX.
25 FT. WEST OF AN OLD FENCELINE.

COMPASS DECLINATION: 20° EAST

8-4-75

Gary J. Langley

CLEVE. GOODWIN

A. VIC CANGIE

M. LENORA LADIG

OK
Jhel