

T245

31	32
6	5

R
S
W

WITNESS CORNER

T255

CORNER LOCATION DETERMINED BY SINGLE PROPORTIONATE MEASUREMENT.

AT THE WITNESS CORNER, WHICH BEARS NORTH 25° FT. FROM THE TRUE CORNER, WE SET A 1" x 24" I. PIPE WITH BRASS CAP ATTACHED, MARKED:

DOUGLAS CO. SURVEYOR

T245

W.C. 25' SOUTH

R	531	532
S		
W	56	55

T255

1975

FLUSH IN THE GROUND, AND MARK THE

FOLLOWING BEARING TREES FOR THE

C. S. File No. 57/34-12

DIETZGEN NO. 385-B

94
245
1307265

WITNESS CORNER;

A 6" ASH BEARS S 80° W 21 $\frac{3}{4}$ FT.,
SCRIBED "WC T24S R5W S31 CSBT"
ON A DOUBLE BLAZE

AND AN 8" W. OAK BEARS S 24° E 3 $\frac{6}{16}$ FT.,
SCRIBED "WC T24S R5W S32 CSBT"
ON A DOUBLE BLAZE.

NOTE:

THIS CORNER IS LOCATED APPROX. 30 FT.
NORTH OF THE CENTERLINE OF A CREEK.

COMPASS DECLINATION: 20° EAST

8-4-75

Gary L. Langitz

CLELL E. GOODWIN

M. LENDRA LADIG

A. VIC CANGIE.

OK
JHL