

9-30-75 ①

T 265 R1W

S 26

—\*—

S 35

FD: 6" x 4" x 5" STONE SCRIBED  
1/4 ON NORTH FACE FROM  
WHICH A 18" STUMP WITH VISIBLE  
SCRIBE BEARS S 35° E 17<sup>8</sup> FT  
AND A ROTTED 10" STUMP BEARS  
N 75° E 9<sup>3</sup> FT

NEW: WE SET AT THE CORNER A  
1 1/2" x 30" IP WITH BRASS CAP  
STAMPEA"

DOUGLAS CO. SURVEYOR

T 265 R1W

S 26

1/4

S 35

1975

WE SET THE STONE ALONGSIDE

FROM WHICH:

A 15" HEMLOCK SCRIBED " 1/4  
S 35 CSBT" IN A DOUBLE

#711 1/2 c

FILE NO. 57/36-12

DIETZGEN NO. 385-6

BLAZE BEARS S 4 1/2° E 33 1/4 FT.

A 18" FIR SCRIBED " 1/4 S 26

CSBT" IN A DOUBLE BLAZE

BEARS N 23 1/2° W 74 3/4 FT.

COMPASS DECLINATION 20° EAST

9-30-75

CLELL GOODWIN

VIC CANGIE

LENORA LADIG

NOTE: CORNER LIES APPROX.

50' SOUTH OF ROAD TO ROCK

PIT AND ON WEST EDGE OF

CLEAR CUT.

*OK*  
*[Signature]*

DIETZEN NO. 385-6

5/1

C.S. No. 57/36-12