

10-13-75

29 | 28 T263 RIW

FD:

BOTH ORIGINAL BEARING TREES WHICH ARE NOW STUMPS. WE OPEN BOTH STUMPS AND FIND GOOD SCRIBING ON BOTH.

THE POSITIONS OF THE ORIG. BT'S IS SUCH THAT THE RECORD DISTANCES WILL NOT INTERSECT. WE FIND THAT A POINT ESTABLISHED AT RECORD BEARING AND DISTANCE FROM THE NE STUMP ALSO CAUSES THE BEARING TO THE SW STUMP TO AGREE WITH THE RECORD BEARING.

AT THE CORNER POINT AS DETERMINED PER THE ABOVE EXPLANATION, WE SET A $\frac{5}{8}$ " X 30" IRON ROD WITH ALUMINUM CAP ATTACHED, MARKED:

DOUGLAS CO. SURVEYOR

29 | 28

1975

C. S. File No. 5736-16 PAGE 1

DIETZGEN NO. 385-6

#10

FROM WHICH :

AN ORIG. 24" D. FIR NOW A 28" STUMP
BEARING N 50° E 13² FT. (RECORDED
N 50° E 13² FT.)

AND AN ORIG. 24" D. FIR, NOW A 28" STUMP
BEARING S 67° W 19⁴ FT., (RECORDED
S 67° W 13² FT.)

WE MARK THE FOLLOWING NEW BT'S,

A 16" HEMLOCK BEARS S 14° E 101³ FT.,
SCRIBED "1/4 S 28 CS BT" ON A DOUBLE
BLAZE.

AND A 7" HEMLOCK BEARS N 69¹/₂° W 83² FT.,
SCRIBED "1/4 S 29 CS BT" ON A DOUBLE
BLAZE.

COMPASS DECLINATION SETTING: 20° EAST

10

[Handwritten signature]

10-13-75

[Handwritten signature]
CELLE E. GODDWIN
A. VIC CARGIE
M. LENDRA LADIG.

C. S. File No. 57/36-16