

T 31 S R 2 W
EAST 1/4 COR
S 20

RENEWAL

FOUND

1. A ROTTED HEMLOCK, 12 INCH DIAMETER
BROKEN OFF APPROXIMATELY 1 FOOT
ABOVE GROUND, STUMP FIRMLY IN
PLACE BEARS S 50° W, 14⁵
FEET. DOWNED TREE IS SCRIBED
"1/4 S 20 BT".
2. ROTTED, BURNED REMAINS OF A
FIR, DIAMETER INDETERMINATE,
BEARS N 27° W, 16⁵ FEET.

RENEWAL

1. SET BRASS CAP AT EAST QUARTER
CORNER OF SECTION 20, STAMPED;

"COUNTY SURVEYORS OFFICE"

T 31 S R 2 W

1/4 S 20

1975

✓
#162

G. S. File No. 57/39-33

RENEWAL

2. SET SPIKE IN 36 INCH DIAMETER FIR
STUMP, BEARS N 27° W, 40³ FEET.
SPIKE STAMPED "B 0 1".

3. SET SPIKE IN 42 INCH DIAMETER FIR
STUMP, BEARS N 73° W, 57² FEET.
SPIKE STAMPED "B 0 2".

NOTE: THE WEST 1/4 CORNER OF
SECTION 21 BEARS N 2° W, 163⁹ FEET,
(REC. N 0° 3' W, 144⁹ FEET).

MAG. DEC. 20° E

12-15-75

L.E. MOWREAU

P.L.E.

J.H.C.

OK *[Signature]*

~~C.S. FILE NO. 57/39-33~~