FORM 711 1-69

PUBLIC LAND CORNERS

FILED
RECEIVED
DEC 22 1980
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

WEYERHAEUSER COMPANY

SPRINGFIELD BRANCH

TOWNSHIP	26S	RANGE	2W
SECTION	6	CORNER	SE
COUNTY	Douglas	OREGON	

GLO Survey Record - 1959	Present condition 4/15/1977
Set brass cap from evidence of original	Decl. 20°E
1883 Bearing Trees.	Brass cap in place.
1. 13" Madrone N51½E 24 lks with a	Down or broken remains of Madrone,
burned and rotted center (record	N51½E 15.8' to root hole. (Not found
bearing N45E	by Weyerhaeuser Co. 7/7/19767 record).
2. 20" Madrone, down and rotted S50E	Evidence of old Madrone scattered by
47 links.	logging at approximate location.
	(W. Co. 7/7/1967 record said no trace).
3. 37" Fir S61W 32 lks with illegible	Down 38" Fir (W. Co. 7/7/1967 record
bark scribes (Record bearing S55W).	identified this BT S60½W 21.6').
4. 45" Fir N12½W 58 lks with an opened	50" Fir (W. Co. 7/7/1967 record identified
and burned blaze.	this BT N12W 38.1').
5. 13" Fir N25E 130 lks 85.8'.	Down 16" Fir, face partly healed, BT tag.
	(W. Co. 7/7/1967 record identified this
	BT N25E 85.7').
6. 19" Fir S71½E 90 lks, 59.4'.	28" Fir stump, face and plates intact.
	(W. Co. 7/7/1967 record identified this
	BT S71E 59.6').
7. 20" Fir S40½W 87 lks, 57.4'.	22" Fir, down healed face and plate intact
	(W. Co. 7/7/1967 record identified this BT
	S40W 58.0').

118

G. S. File No. 58/8-48c

CONTINUED PUBLIC LAND CORNERS - Weyerhaeuser Company - Springfield

CORNER: SE Section 6, Township 26S, Range 2W

GLO Survey Record - 1959	Present condition 4/15/1977
8. 38" Fir N21½W 55½ lks, 36.6'.	48" Fir, face and plate intact (W. Co. 7/7/1967 record identified this BT N22W 36.6').
Weyerhaeuser Company Survey Record by H. E. Case, L. Warren 7/7/1967.	
Found evidence of GLO 1883 and 1959 accessories.	As recorded above.
Referenced 1959 GLO Brass Cap with W nails and plates: (Decl. 20°E).	
5. 14" Fir N25E 85.3' 1959 GLO BT	As recorded above.
6. 28" Fir S71E 58.5' 1959 GLO BT.	As recorded above.
3. 38" Fir S64W 20.2' 1883 GLO BT.	As recorded above.
8. 48" Fir N21½W 34.7' 1959 GLO BT.	As recorded above.
Accessories added this date 4/15/1977 By: Glen McChesney Decl 20°E.	Under the supervision of:
W nails and plates on:	
40" Fir stump N56E 59.2'.	
54" Fir stump N64E 65.2'.	

FILED
RECEIVED
DEC 22 1980
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

REGISTERED PROFESSIONAL LAND SURVEYOR

Frank O. Williams

OREGON
JULY 12, 1966
FRANK O. WILLIAMS
0875

C. S. File No. 58/8-48