

SUBDIVISION OF SECTION 10  
T26S, R9W, W.M.  
DOUGLAS COUNTY, OREGON  
WILLIAMS RIVER NO. 2 SURVEY

General Information

This survey was conducted in order to establish the location of Company property within the section. Equipment used on the survey included a wild T-16ED theodolite and a 300 foot K & E "invincible" chain. The survey was initiated at the southwest corner of the section and consisted of a control traverse around the section and an interior traverse around Company ownership. Error of closure of the control traverse was 1/12,000 and that of the interior traverse was 1/7100. The east and south 1/4 corners were missing and had to be re-established. All courses shown on the survey plat are based on a solar observation.

Corner Research

The following corners and/or their accessories were either found or set as indicated during the survey. Weyerhaeuser Company location poster and "W" nails were used on all reference points.

SW Corner

\*16 ✓ Found a B.L.M. monument from which:

16" Douglas Fir bears S40°W, 57 LKS  
10" Hemlock bears S47°E, 31 LKS  
10" Maple bears N13°E, 38 LKS  
12" Douglas Fir bears N28°W, 45 LKS

There is also a 2" aluminum pipe set by Menasha Corp.  
It is improperly located according to B.L.M. sources  
and G.L.O. notes.

S 1/4 Corner

\*17 ✓ No evidence of the original corner or its accessories was found.  
The corner was re-established by the single proportion method.

Set a 1" iron pipe from which:

12" Madrone bears N81°W, 32.0 feet scribed 1/4 Cor S 10 RP  
24" D. Fir bears S82°E, 29.1 feet scribed 1/4 Cor S 15 RP

SE Section Corner

Found a B.L.M. monument from which:

- #8 ✓  
20" Cedar bears S30°W, 25 LKS - original scribe visible  
10" Myrtle bears N65 1/2°E, 65 LKS  
36" Myrtle bears S03°W, 27 LKS

E 1/4 Corner

- #9 ✓ No evidence of the original corner or its accessories was found.  
The corner was re-established by the single proportion method.

Set a 1" iron pipe from which:

- 24" D. Fir bears S43°W, 36.1 feet scribed 1/4 Cor S 10 RP  
14" Madrone bears S60°E, 12.0 feet scribed 1/4 Cor S 11 RP

NE Section Corner

- #10 ✓ Found 1" iron pipe set by Weyerhaeuser Company engineers. Original bearing trees for pipe were destroyed by road construction. Corner was re-referenced as follows:

- 8 " Hemlock bears N37°W, 6.1 feet  
24" Madrone bears N76°E, 5.5 feet  
18" D. Fir stump bears S13°E, 25.0 feet  
8 " D. Fir bears S60°W, 23.4 feet

N 1/4 Corner

- #11 ✓ Position of this corner is occupied by a small hemlock stub. Original bearing trees were destroyed by road construction. Re-referenced by Weyerhaeuser Co. engineers

- 22" Hemlock bears N01°W, 17.9 feet  
28" D. Fir bears S69 1/2°E, 30.0 feet

NW Section Corner

- #12 ✓ The original corner and its accessories were destroyed by road construction. Before its destruction, the corner was re-referenced by Weyerhaeuser Company engineers.

1" Iron pipe from which:

- 36" Red Cedar bears N78°E, 59.0 feet  
36" Douglas Fir bears N39°W, 21.8 feet

W 1/4 Corner

#13 ✓ Restored during Williams River No. 1 Survey (Sec 9, T26S, R9W)

Set 2" iron pipe from which:

14" Maple bears S73 1/2°W, 11.5 feet

10" Maple bears S61 1/2°E, 8.0 feet

Subdivision Corner

#14 ✓ C 1/4 Corner

Drove nail in 2 foot by 3 foot rock outcropping.

Referenced as follows:

36" D. Fir bears N67W, 15.6 feet scribed C 1/4 Cor S 10 RP

12" Cedar bears N46 1/4°E, 13.4 feet scribed C 1/4 S 10 RP

Respectfully Submitted  
Robert C. Adamek  
Weyerhaeuser Company  
Dellwood District Engineer

Approved

  
H. R. Reppeto  
Region Engineer