

**MAX H. HULL Land Surveying**

713 N. E. 7th Street Grants Pass, Oregon 97526

SURVEY NARRATIVE to comply with paragraph 209.250, O. R. S.

DATE: May 7, 1975

FOR: Mr. Robert Burrows
Box 100 Mt. Reuben Rd.
Glendale, Oregon

PURPOSE: To Survey the North 1/2 of the Northeast 1/4 of the Southwest 1/4 of the Northwest 1/4 of Section 2, Township 33 South, Range 7 West, Willamette Meridian, Douglas County, Oregon.

PROCEDURE: Using a Wild T-2E Theodolite and a Tellurometer CA-1000 I established control on the following corners:

Center 1/4 corner at which point I found a 5/8" Iron Rod from which
A Madrone 7 ins. diam. bears North 36° West 2.90 feet
A Madrone 5 ins. diam. bears North 67° East 34.84 feet
A Madrone 5 ins. diam. bears South $42^{\circ}45'$ East 73.25 feet
A P. Pole bears South $26^{\circ}15'$ West 77.92 feet

West 1/4 corner at which point I found a 3/4" Iron Pipe from which
A Chinquapin 10 ins. diam. bears South 44° West 26.6 feet
A Madrone 12 ins. diam. bears North 45° East 21.6 feet

North 1/16 corner at which point I found a Brass Cap from which
A Fir 6 ins. diam. bears North 61° West 21.5 feet
A Fir 7 ins. diam. bears South 11° West 143.4 feet

Northwest 1/16 corner at which point I found a 5/8" Iron Rod with aluminum cap from which
A Fir 8 ins. diam. bears South 2° West 117.9 feet
A Pine 22 ins. diam. bears North 34° East 81.3 feet

I also made ties to the Northwest Section corner and the North 1/4 corner of said Section 2 to check the position of the Northwest 1/16 corner. Finding that said Northwest 1/16 corner checks with reasonable accuracy, I computed the subdivision of the Southwest 1/4 of the Northwest 1/4; thence starting at said Northwest 1/16 corner, I surveyed South $0^{\circ}12'31''$ West 367.62 feet and set a 5/8" Iron Rod; thence I surveyed South $89^{\circ}19'09''$ West 224.68 feet and

C.S. File 58152AMap File M57127



Office 476-2425

MAX H. HULL Land Surveying

713 N. E. 7th Street Grants Pass, Oregon 97526

set a witness corner on the West bank of Cow Creek; thence I continued South $89^{\circ}19'09''$ West 426.99 feet and set a 5/8" Iron Rod; thence I surveyed North $0^{\circ}05'41''$ East 368.56 feet and set a 5/8" Iron Rod; thence North $89^{\circ}24'10''$ East 370.47 feet and set a witness corner on the West bank of Cow Creek.

Meridian, is based on Survey No. M41-39.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Max H. Hull
OREGON
JULY 11, 1969
MAX H. HULL
901

C.S. File 58-152b

Map File M57-37