

FILED ✓
RECEIVED 24TOWNSHIP 32 SOUTH
RANGE 2 WEST

APR 28 1976

COUNTY SURVEYOR

Re-establishment of Quarter corner common to sections 27 & 28
JACKSON COUNTY, ORE.Re-establishment of Quarter corner common to sections 29 & 28
refer to recorded survey #4379 ✓

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 23 and 24, Twp. 32 South, Range 2 West, W.M. V=18 1/4°
Fd., firmly set, the 14 X 8 X 10 ins. stone, projecting 3 ins. and mkd. "1/4" on West face. Recorded as 24 X 12 X 8 ins. by C.L. Campbell in 1902.

I replaced said stone with a 1 X 36 ins. G.I. pipe set 26 ins. in the ground with a 2 1/2 ins. bronze disc mkd.:

Jackson County 1975
T32S R2W
1/4S
23 + 24

Original B.T.'s fd. as follows:

A White Fir, 25 ins. dia., with healed blaze, bears record, N86°E, 29.70 ft. to center of tree.

A White Fir, 30 ins. dia., with healed blazes, bears S24°W, 28.38 ft. to center of tree. Record, S33°W, 28.38 ft.

I deposit original stone alongside as a memorial, mkd. new trees C.S. B.T. and take measurements to center of trees at lower blaze:

White Fir, 13 ins. dia., bears S6 1/2°E, 19.15 ft.

White Fir, 12 ins. dia., bears N63 1/2°W, 13.27 ft.

Corner lies 40 ft. North of small draw, and about 1,000 ft. North of location marker on 30 ins. dia., Fir snag, alongside road.

June 17, 1975

R. Frost

G. Cunningham

D. Gaylord - U.S.F.S.

Approved by: Ed McGinty
Co. Surveyor

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 24 and 25, Twp. 32 South, Range 2 West, W.M. V=21 1/2°

Fd., 13 X 10 X 10 ins. stone (record, 18 X 12 X 10 ins.) firmly set, projecting 5 ins. and mkd. "1/4" on North face, as recorded by C.L. Campbell in 1902.

I replace said stone with a 1 X 36 ins. G.I. pipe set 30 ins. in the ground with a 2 1/2 ins. bronze disc mkd.:

Jackson County 1975
T32S R2W
1/4S 24
25

An original B.T., now a sawed D. Fir stump, 28 ins. dia., containing reverse impression of scribed (partial) "T", bears record N55°E, 25.08 ft. The S.W. B.T. now gone.

Deposit original stone alongside corner as a memorial, mkd. the following trees C.S. B.T. and take measurements to center of trees at lower blaze:

D. Fir, 14 ins. dia., bears N48 1/4°E, 28.37 ft.

W. Fir, 5 ins. dia., bears S80°W, 20.01 ft.

Corner lies on South slope, about 100 ft. North of road.

June 17, 1975

R. Frost

G. Cunningham

D. Gaylord, U.S.F.S.

Approved by: Ed McGinty
Co. Surveyor