

M 63-19

FILED
RECEIVED

WEYERHAEUSER COMPANY
SKIP CREEK SURVEY NARRATIVE
SECTION 2, T. 26 S., R. 9 W. W. M.
DOUGLAS COUNTY, OREGON

FEB 23 1977

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

General Information

In order to establish the location of Company property in Section 2, T. 26 S., R. 9 W., W.M., a survey was conducted using a Wild T-16 ED theodolite, K and E "Invincible" 300 foot chain, Jena 020A theodolite, and a Mac I electronic distance meter. The survey was initiated at the S.E. corner of the section and consisted of a control traverse around the section and two inner traverses around the foreign (B.L.M.) ownership. Error of closure of the control traverse was 1/7,000. 1/9,000 and 1/5,000 were the closures of the North and South inner loops. The terrain is brushy, precipitious and difficult to survey. All bearings on the accompanying plat are based on a solar observation.

Corner Research

The following corners and/or their accessories were either found or set as indicated during the survey. Weyerhaeuser Company location posters and "W" nails were used on reference points for established corners. Additional information may be found in Weyerhaeuser Company's Williams River No. 2 (3-27-75) and Cedar Creek (9-23-74) surveys.

S.E. Section Corner

Found 1" iron pipe from which a:
30" Douglas Fir bears N 21° E, 41.2 feet
16" Douglas Fir bears S 55 1/2° E, 46.1 feet
48" Douglas Fir bears S 12° W, 57.6 feet

For additional information see Weyerhaeuser Cedar Creek survey.

S 1/16 Corner East Line

Set 3/4" iron pipe from which a:
24" Cedar bears N 88° E, 44.18 feet scribed S 1/16 CNR RP
13" Hemlock bears S 67 1/2° W, 39.88 feet scribed S 1/16 CNR RP

E. 1/4 Corner

Found no trace of original corner or its accessories. Restored this corner by the single proportion method.

Set 3/4" iron pipe from which a:
24" Alder bears S 51 3/4° W, 27.96 feet scribed 1/4 CNR RP
24" Hemlock bears N 24° E, 20.25 feet scribed 1/4 CNR RP

N. 1/16 Corner East Line

Set 3/4" iron pipe from which a:

9" Hemlock bears S 86 1/2° E, 38.17 feet, scribed N 1/16 CNR RP
15" Hemlock bears S 36° W, 28.48 feet, scribed N 1/16 CNR RP

FILED
RECEIVED

N.E. Section Corner

Found one original bearing tree with visible scribe marks:
36 1/2" Douglas Fir bears N 58° E, 78 LKS

FEB 23 1977

N. 1/4 Corner

COUNTY SURVEYOR
DEUEL COUNTY, ORE.

Found no trace of the original corner or its accessories. Restored this corner by the single proportion method.

Set 3/4" iron pipe from which a:

19" Douglas Fir bears N 49 1/2° W, 7.5 feet scribed 1/4 CNR RP

14" Douglas Fir bears S 22° W, 12.6 feet scribed 1/4 CNR RP

#16

N.W. Section Corner

Found two original bearing trees with visible scribe marks:

16" Cedar bears S 23° W, 35 LKS. A larger Cedar now stands between this bearing tree and the corner.

48" Douglas Fir bears N 43° W, 82 LKS.

Set 3/4" iron pipe

#17

W. 1/4 Corner

Found no trace of the original corner or its accessories. Restored this corner by the single proportion method.

Set 3/4" iron pipe from which a:

40" Cedar stump bears N 12 3/4° E, 44.3 feet

#18

S.W. Section Corner

Found 1" iron pipe from which a:

8" Hemlock bears N 37° W, 6.1 feet

24" Madrone bears N 76° E, 5.5 feet

18" Douglas Fir stump bears S 13° E, 25.0 feet

8" Douglas Fir bears S. 60° W, 23.4 feet

For additional information see Weyerhaeuser Williams River No. 2 survey.

S. 1/4 Corner

Found no trace of the original corner or its accessories. Restored this corner by the single proportion method.

Set 3/4" iron pipe from which a:

42" Douglas Fir bears N 65° E, 21.5 feet

18" Cedar bears S 79° W, 7.9 feet

#19

C.S. 1/16 Corner

Set 3/4" iron pipe from which a:

28" Douglas Fir bears N 36° E, 13.4 feet scribed C S 1/16 RP

20" Cedar bears N 71° W, 8.8 feet scribed C S 1/16 RP

FILED
RECEIVED

FEB 23 1977

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

C 1/4 Corner

Set 3/4" iron pipe from which a:

27" Douglas Fir bears S 06° W, 21.7 feet scribed C 1/4 RP

29" Douglas Fir bears N 52° E, 27.6 feet scribed C 1/4 RP

#20

CN 1/16 Corner

Set 3/4" iron pipe from which a:

24" Douglas Fir bears due North, 12.9 feet scribed CN 1/16 RP

26" Douglas Fir bears S 13° W, 12.8 feet scribed CN 1/16 RP

Respectfully submitted,

Robert C. Adamek
Weyerhaeuser Company
Dellwood District Engineer

REGISTERED
PROFESSIONAL
LAND SURVEYOR

APPROVED:

Robert C. Adamek

OREGON
JULY 10, 1972
ROBERT C. ADAMEK
909

Henry R. Reppeto

H. R. Reppeto
Region Engineer

50/135C