



**COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE**

FILED ϕ

RECEIVED \checkmark

APR 15 1980

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE. ϕ

SURVEY TO SET CORNERS

LOCATED IN N.W. 1/4,
SECTION 27, TOWNSHIP 30 SOUTH,
RANGE 5 WEST, WILLAMETTE MERIDIAN,
DOUGLAS COUNTY, OREGON.
LOT 7 & 8, RODMAN SUBDIVISION,
CITY OF CANYONVILLE, OREGON.

NORTH

PREPARED FOR:

**MARCH 1, 1980
SCALE: 1" = 50'**

**GARY AND ANNA JONES
P. O. BOX 142
CANYONVILLE, OREGON 97417
phone: 839-6370**

LEGEND

- FOUND 1/2" IRON PIN (as per VOL. 8, PG 41).
- SET 5/8" IRON PIN

JOHN H. MARKHAM JR.
OSPE & RPLS
MYRTLE CREEK, OREG.
ph. 863-4590

DRAWN BY
RAYMOND F. BROWN
P.O. BOX 539
CANYONVILLE, OREG.
ph. 839-6185

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
SEPTEMBER 23 1977
JOHN H. MARKHAM, JR.
1261

w/survey COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE

LOT SURVEY for GARY and ANNA JONES in the Northwest $\frac{1}{4}$, Section 27,
Township 30 South, Range 5 West, Willamette Meridian, Douglas County,
Oregon.
Lot 7 and 8, Rodman Subdivision, City of Canyonville.

Survey began at the Southwest corner of Lot 7, Rodman Subdivision
which is a 1/2 inch iron pin. Field investigation also found the Southwest
corner and the Northwest corner of Lot 5, Rodman Subdivision which were
115.00 feet apart.

I now set at the mentioned Southwest corner of Lot 7 and sight the
Southwest corner of Lot 5 which bears West 100.00 feet (vol 8, pg 41),
thisline was used as my "Base of Bearing".

I now run East 100.00 feet and set a 5/8 inch iron pin at the South-
east corner of Lot 8.

I now return to the Southwest corner of Lot 7 and run North 115.00
feet and set a 5/8 inch iron pin at the Northwest corner of Lot 7.

I now go to the mentioned Southeast corner of Lot 8 and run North
115.00 feet and set a 5/8 inch iron pin at the Northeast corner of Lot 8.

FILED
RECEIVED *z/h*

APR 15 1980

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

DATE OF SURVEY: March 1, 1980
SURVEYOR: John H. Markham Jr.
Myrtle Creek, OR.
ph 503-863-4590

