

CERTIFIED RECORD OF CORNER PERPETUATION

This corner was set originally by Rufus Moore in 1883 and subsequently re-established by Hans W. Thielsen in 1955 from the original record of Moore.

T32S, R1W, W.M.
9/10
16/15

I find a 2 inch outside diameter iron pipe, firmly set with a brass cap attached, from which the bearing trees recorded by Thielsen were found as follows:

- A D. Fir 14" diam. bears N 14 $\frac{1}{2}$ ^oE. 18.4 ft. (record N 14 $\frac{1}{2}$ ^oE. 18.5 ft.)
- A D. Fir 9" diam. bears N 29 $\frac{1}{2}$ ^oW. 22.7 ft. (record N 29 $\frac{1}{2}$ ^oW. 23.1 ft.)

I perpetuate the corner position by taking the following new bearing trees and place a brass washer bearing my registration No. in the lower blaze:

- A D. Fir 13" diam. marked "T32S R1W S16BT" bears S. 34 $\frac{1}{2}$ ^oW. 24.8 ft.
- A D. Fir 12" diam. marked "T32S R1W S15BT" bears S. 43 $\frac{1}{2}$ ^oE. 34.1 ft.

Va. 18 $\frac{1}{2}$ ^o

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Hurt C Weaver

OREGON
JULY 14, 1978
KURT C. WEAVER
1679

I hereby certify the above corner perpetuated as herein described on November 16, 1978.

Witnesses :

Herb Farber
Reg Harding

Office of Surveyor, County of Douglas,
State of Oregon, I hereby certify that the within
instrument was filed in this office for record on
8 th day of December, 1978.

Francis L. Ingram by *Virginia A. Saugen*
County Surveyor Deputy

dh

#69 ✓