


CERTIFIED RECORD OF CORNER PERPETUATION

This corner was originally set by Rufus Moore in 1883 and subsequently re-established by Hans W. Thielsen in 1955 from record evidence of Moore.



I find a 1 inch outside diameter iron pipe with brass cap firmly set for the corner from which the original bearing tree taken by Moore found as follows:

A D. Fir Snag 8" Diam. bears N 76 1/2° W 16.9 feet (record N77° W 15.8 ft.)

I find the bearing trees taken by Thielsen as follows:

A D. Fir 34" diam. bears N 56 1/2° W 17.9 feet (record N 55 1/2° W 17.2 ft.)  
A D. Fir stump 33" diam. bears S 55 1/2° E 36.2 Ft. (record S 55 1/2° E 36.3 ft.)

I perpetuate the corner position by taking the following new tree and place a brass washer bearing my registration no. in the lower blaze:

A D. Fir 22" diam. marked 1/4 S BT bears N 62° E 23.7 ft.  
Va. = 21 1/2°

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Kurt C. Weaver*

OREGON  
JULY 14, 1978  
KURT C. WEAVER  
1679

I hereby certify the above corner perpetuated as herein described on November 16, 1978.

Witnesses:

Herb Farber  
Reg Harding

Office of Surveyor County of Douglas  
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 8th day of December.

Francis L. Ingram by *Virginia A. Langen*  
County Surveyor Deputy

*JK*  
RECORDED  
INDEXED  
NOV 20 1978  
CLERK OF COUNTY

#68 ✓

C. S. File No. 58/176-7