

FILED  
RECEIVED *JK*

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

RECEIVED  
SURVEYOR  
OF DOUGLAS  
COUNTY

This corner was originally established by Rufus Moore in 1883 and subsequently re-established by John H. Markham Jr. in April, 1959.

7325, R1W, W.M.  
 $\frac{1}{4} \frac{4}{9}$

I find a 1½ inch iron pipe with a union and elbow, firmly set and exposed 11 inches in a mound of stone. I find the following tree marked by Moore:

A Douglas Fir 38 inches in diam. bears N 25°50'W 11.0 ft. (record N 25°W 11.9 ft.).

*Len #8*

I find the following trees marked by Markham:

A Douglas Fir 48 inches in diam., bark scribed ¼ S 9 BT bears S 3°40'W 33.5 ft. (record S 2°W 33.5 ft.)

A Maple 10 inches in diam. bears S 40°23' W 27.0 ft. (record S 40°W 26.5 ft.).

A Dead and down Douglas Fir 12 inches in diam. bears record N 4°E 35.2 feet to stump depression.

I set a 2 inch diam. x 30 inch G.I.P. in the exact position of the found monument, with a 2½ inch brass cap marked:

Va = 21°

7325 R1W  
 $\frac{1}{4} \frac{54}{59}$   
15 1679 1979

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Kurt C Weaver*  
OFFICE  
DEPT. OF LAND  
KURT C. WEAVER  
1979

I hereby certify the above corner perpetuated as herein described on February 15, 1979.

Witnesses:

Herb Farber  
Reg Harding  
Bill Trempe

Office of Surveyor, County of Douglas, State of Oregon, I hereby certify that the within instrument was filed in this office for record on 22 nd day of March, 1979.

Francis L. Ingram by *Virginia A. Ruzger*  
County Surveyor Deputy

#73 *+*

S. File No. 581176-24