

TOWNSHIP 30 SOUTH
RANGE 3 EAST

FIRST RE-ESTABLISHMENT

Quarter corner common to Secs. 12 and 13, Twp. 30 South, Range 3 East, W.M. V=19°

Fd, projecting 5 ins. (13 cm) the original 1 ins. (2.5 cm) diam. iron pipe with standard G.L.O. brasscap mkd:

1/4 $\frac{S12}{S13}$
1928

as recorded by H. Raymond in 1928.

Original bearing trees fd as follows:

the base of a down Pine, 16 ins. (41 cm) diam., with healed single blaze, brs record; N73-1/2E, 49.5 ft. (15.09 m).

the roothole of a tipped over Pine, 10 ins. (25 cm) diam., scribed "1/4 S13 BT" brs record; S44E, 33.66 ft. (10.26 m).

I mk new trees CS BT and take measurements to center of trees at lower blaze:

hemlock, 21 ins. (53 cm) diam., brs S34-1/2E, 35.19 ft. (10.73 m).

hemlock, 7 ins. (18 cm) diam., brs N4-1/2W, 39.32 ft. (11.98 m).

Corner lies 30 ft. (9 m) East of the top of small spur C. N-S which slopes (70%) West into creek and 65 ft. (20 m) East of creek and an estimated 125 ft. (38 m) North of same creek.

August 29, 1978
B. Malotte
R. Frost

Approved by: Ed McGinty
Co. Surveyor

1/4 Sec 12 Doug Co.

FIRST RE-ESTABLISHMENT

Quarter corner common to Secs. 11 and 12, Twp. 30 South, Range 3 East, W.M. V=19°

Fd, projecting 3 ins. (8 cm) in large mound of stone the original 1 in. (2.5 cm) diam. iron pipe with G.L.O. brasscap mkd:

1/4S
S11 | S12
1928

Original bearing trees recorded by H. Raymond in 1928 fd as follows:

sawed fir stump, 28 ins. (71 cm) diam. scribed "1/4S12 BT" in exposed face, brs N39-1/2E, 29.30 ft. (8.93 m) to center. Record; N35-1/2E, 28.38 ft. (8.65 m).

douglas fir, 39 ins. (99 cm) diam., scribed "1/4S11 BT" brs N24-1/2W, 44.52 ft. (13.57 m). Record; N24-1/2W, 44.88 ft. (13.68 m).

I mk a new tree CS BT:

douglas fir, 5 ins. (13 cm) diam., brs N87E, 20.20 ft. (6.16 m) to center of tree at lower blaze.

August 28, 1978
B. Malotte
R. Frost

Approved by: Ed McGinty
Co. Surveyor

DN Doug. Township
LINE

#2#4 ✓
T30-3E

FILED
RECEIVED

NOV 20 1978

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.