

Raymond 7.

TOWNSHIP 30 SOUTH
RANGE 3 EAST

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 32 only, Twp. 30 South Range 3 East, W.M. $V=20^\circ$
Fd, projecting 8 ins. (20 cm.), the original 1 ins. (2.5 cm.) diam. iron pipe, with G.L.O. brasscap mkd:

1/4 S32
1928

as recorded by H. Raymond in 1928.

The single remaining original bearing tree, a hemlock now 16 ins. (41 cm.) diam., with healed single blaze, brs record; N29°E, 48.18 ft. (14.69 M.) on slope, to center. Re-measured; 47.70 ft. (14.54 M.) to center of tree.

I mk new trees CS BT and take measurements to center of trees at lower blaze:

douglas fir, 13 ins. (33 cm.) diam., brs S13 1/2°E, 20.20 ft. (6.16 M.).

hemlock, 12 ins. (30 cm.) diam., brs S83 1/2°W, 4.40 ft. (1.34 M.).

Corner lies about 15 ft. (5 M.) East of shoulder of road cutbank.

B. Malotte
T. Walker

Approved by: Ed McGinty
County Surveyor

FIRST RE-ESTABLISHMENT

Section corner common to Sec. 24 and 25, Twp. 30 South, Range 3 East, and Sec. 19 and 30, Twp. 30 South, Range 4 East, W.M.

SEE PAGE 19, TWP. 30 SOUTH, RANGE 4 EAST, W.M.

FIRST RE-ESTABLISHMENT

Section corner common to Secs. 15, 16, 21 and 22, Twp. 30 South, Range 3 East, W.M. $V=19^\circ$

Fd, projecting 12 ins. (30 cm) in mound of stone, the original 2 ins. (5 cm) diam. iron pipe with standard G.L.O. brasscap mkd:

T30S R3E
S16 | S15
S21 | S22
1928

as recorded by H. Raymond in 1928.

Original bearing trees fd as follows:

hemlock, 11 ins. (28 cm) diam., with healed single blaze, brs N67E, 39.83 ft. (12.14 m) to center. Record; N67E, 40.26 ft. (12.27 m).

hemlock, 17 ins. (43 cm) diam., with scribe marks visible in partially healed single face brs record S4-1/2E, 50.16 ft. (15.29 m) to center.

fir stub, 50 ins. (127 m) diam., containing scribe marks including "S21BT" in partially exposed face, brs record; S69W, 5.28 ft. (1.61 m) to center.

Original NW-BT now gone.

I mk new trees CS BT and take measurements to center of trees at lower blaze:

douglas fir, 11 ins. (28 cm) diam., brs S27W, 52.60 ft. (16.03 m).

hemlock, 11 ins. (28 cm) diam., brs N69W, 92.66 ft. (28.24 m).

Corner lies near top of SE ridge, 55 ft. (16.8 m) East of center of (under construction) road.

August 23, 1978
B. Malotte
R. Frost

Approved by: Ed McGinty
Co. Surveyor

FILED
RECEIVED
NOV 20 1978
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE

U.S. File No. 581102-4

*UW Doug - Jackson
CO. LINE*

#5
T30-3E