


Douglas

TOWNSHIP 30 SOUTH  
RANGE 4 EAST

FIRST RE-ESTABLISHMENT

Section corner common to Secs. 34 and 35, Twp. 29 South, Range 4 East and Secs. 2 and 3, Twp. 30 South, Range 4 East, W.M. V=20°

Fd bent over, the original 2 x 36 ins. (5 x 91 cm) iron pipe with attached G.L.O. brass cap mkd:



as recorded by H. Raymond.

I remove, straighten and replace the above, in the original position, 26 ins. (66 cm) in the ground, from which:

douglas fir, 24 ins. (61 cm) diam., with healed blazes, brs S27E, 25.64 ft. (7.82 m) to center. Record; S27E, 25.74 ft. (7.85 m).

douglas fir, 17 ins. (43 cm) diam., with healed single blaze, brs S56W, 46.32 ft. (14.12 m) to center. Record; S56W, 46.86 ft. (14.28 m).

pine snag, 22 ins. (56 cm) diam. containing scribe marks including "4" and "34 BT" in partly exposed face, brs N57W, 37.88 ft. (11.55 m) to center. Record; N57W, 38,28 ft. (11.67 m).

NE BT now gone.

I mound stones around corner, mk the following trees CS BT and take measurements to center of trees at lower blaze:

white fir, 13 ins. (33 cm) diam., brs N42E, 147.1 ft. (44.84 m).

shasta red fir, 25 ins. (64 cm) diam., brs N83W, 43.0 ft. (13.11 m) to center.

Corner lies approximately 85 ft. (25.91 m) S6E, from location marker on 25 ins. (64 cm) diam. fir, alongside road.

August 7, 1978

J. Swanson

R. Frost #5 T29-4E ✓  
#4 T30-4E ✓


Approved by: Ed McGinty  
Co. Surveyor

C

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 35, Twp. 29 South, Range 4 East and Sec. 2, Twp. 30 South, Range 4 East, W.M. V=18-1/2°

Fd, 2 ins. (5 cm) deep, the 1 in. (2.5 cm) diam. iron pipe with standard G.L.O. brasscap mkd:



as recorded by H. Raymond in 1929.

Original bearing trees fd as follows:

shasta red fir, 25 ins. (64 cm) diam. with healed single blaze brs N18E, 34.66 ft. (10.56 m) to center. Record; N18E, 34.98 ft. (10.66 m).

the NW branch, 20 ins. (51 cm) diam. of a double fir, sawed stumps, brs S83E, 34.5 ft. (10.52 m) to center. Record; S83E, 34.32 ft. (10.46 m).

I mound stones around corner and mk a new tree CS BT:

shasta red fir, 24 ins. (61 cm) diam., brs S29W, 36.64 ft. (11.17 m) to center of tree at lower blaze.

Corner lies about 225 ft. (69 m) South of location marker on 10 ins. (25 cm) diam. fir (mkd with axed "X") alongside road.

August 7, 1978

J. Swanson

R. Frost

Approved by: Ed McGinty  
Co. Surveyor

FILED  
RECEIVED *vh*

NOV 20 1978

COUNTY SURVEYOR  
#6 T29-4E ✓  
#5 T30-4E ✓  
DOUGLAS COUNTY, ORE.

C. S. File No. 58/183-8