Douglas

TOWNSHIP 30 SOUTH
RANGE 4 EAST

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 34, Twp. 29 South, Range 4 East and Sec. 3, Twp. 30 South, Range 4 East, W.M. V=19-1/4°

Fd, projecting 3 ins. (8 cm), the 1 in. (2.5 cm) diam. iron pipe with G.L.O. brasscap mkd:

S34
1/4 —•—
S3
1929

as recorded by H. Raymond in 1929.

Original bearing trees fd as follows:

pine snag, 14 ins. (36 cm) diam., containing scribe mkd in partially exposed face, brs N35E, 21.25 ft. (6.48 m) to center. Record; N35E, 21.12 ft. (6.44 m).

white fir, 16 ins. (41 cm) diam., with healed blazes, brs S58E, 14.84 ft. (4.52 m) to center. Record; S58E, 15.18 ft. (4.63 m).

I mk new trees CS BT and take measurements to center of trees at lower blaze:

hemlock, 14 ins. (36 cm) diam., brs N88E, 28.48 ft. (8.68 m).
white fir, 22 ins. (56 cm) diam., brs S86W, 18.29 ft. (5.57 m).

August 7, 1978
J. Swanson
R. Frost #3 T 29-4E ✓
#6 T 30-4E ✓

Approved by: Ed McGinty
Co. Surveyor

FIRST RE-ESTABLISHMENT

Section corner common to Sec. 36, Twp. 29 South, Range 4 East; Sec. 31, Twp. 29 South, Range 5 East; Sec. 1, Twp. 30 South, Range 4 East and Sec. 6, Twp. 30 South, Range 5 East, W.M. V=19°

Fd, projecting 8 ins. (20 cm) the 3 ins. (7.6 cm) diam. iron pipe with standard G.L.O. brasscap mkd:

T29S
R4E R5E
S36 | S31
S1 | S6
T30S
1929

as recorded by H.N. Raymond in 1929. Original bearing trees fd as follows:

sawed fir stump shell, 36 ins. (91 cm) diam. brs record N32E, 54.78 ft. (16.70 m) to center.

fir snag, 26 ins. (66 cm) diam., containing scribe mkd including "5E S6 BT" in partly exposed single face, brs S80-1/2E, 85.92 ft. (26.19 m) to center. Record; S80-1/2E, 85.14 ft. (25.95 m).

white fir, 38 ins. (97 cm) diam., with healed single blaze, brs S81W, 26.9 ft. (8.20 m) to center. Record; S81W, 28.38 ft. (8.65 m).

shasta red fir, 41 ins. (104 cm) diam. with healed single blaze, brs N36W, 25.9 ft. (7.89 m) to center. Record; N36W, 27.06 ft. (8.25 m).

I mk new trees CS BT and take measurements to center of trees at lower blaze:

white fir, 22 ins. (56 cm) diam. brs N16E, 32.0 ft. (9.75 m).
white fir, 10 ins. (25 cm) diam., brs S83E, 64.78 ft. (19.74 m).

Corner lies at North edge of marshy stream bed, 25 ft. (7.62 m) South of South edge of clear cut and about 400 ft. (122 m) West of location marker on 16 ins. (41 cm) diam. fir alongside road. C N-S.

August 3, 1978
B. Malotte
R. Frost

FILED
RECEIVED
NOV 20 1978
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Approved by: Ed McGinty
Co. Surveyor

#7-T30-4E ✓
#4-T29-4E ✓
#1-T29-5E ✓
#1-T30-5E ✓

C.S. File No. 58/183-9