

Douglas

TOWNSHIP 30 SOUTH
RANGE 4 EAST

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 33, Twp. 29 South, Range 4 East and Sec. 4, Twp. 30 South, Range 4 East, W.M. V=18 1/2°
Fd, projecting 9 ins. (23 cm), the 1 in. (2.5 cm) diam. iron pipe with G.L.O. brasscap mkd:

1/4 $\frac{S33}{S4}$
1929

Original bearing trees recorded by H. Raymond in 1929 fd as follows:

hemlock, 22 ins. (56 cm) diam., with healed single blaze, brs S75-1/2E, 47.85 ft. (14.58 m) to center. Record; S75-1/2E, 48.18 ft. (14.69 m).
fir snag, 15 ins. (38 cm) diam., with healed single blaze, brs N71-1/2W, 37.93 ft. (11.56 m) to center. Record; N70W, 38.28 ft. (11.67 m).

I mk a new tree CS-BT:

white pine, 14 ins. (36 m) diam., brs N64-1/2W, 9.62 ft. (2.93 m) to center of tree at lower blaze.

Corner lies about 300 ft. (91 m) West of location marker on 8 ins. (20 cm) diam. White pine located approximately 50 ft. (15 m) West of road.

August 9, 1978

B. Malotte

R. Frost

Approved by: Ed McGinty
Co. Surveyor

#1 - T30-4E ✓ #7 T29-4E ✓

C

FIRST RE-ESTABLISHMENT

Section corner common to Secs. 35 and 36, Twp. 29 South, Range 4 East, and Secs. 1 and 2, Twp. 30 South, Range 4 East, W.M. V=19-3/4°
Fd, projecting 8 ins. (20 cm) in mound of stone, the original 2 ins. (5 cm) diam. iron pipe with standard G.L.O. brasscap mkd:

T29S R4E
S35 | S36
S2 | S1
T30S
1929

as recorded by H. Raymond in 1929.

Original bearing trees fd as follows:

the stump of a down 9 ins. (23 cm) diam. fir, scribed as recorded, brs N34E, 48.6 ft. (14.81 m) to center. Record; N34E, 48.84 ft. (14.89 m).
white pine, 18 ins. (46 cm) diam., with scribe mkd visible in partly healed blaze, brs S48-1/2E, 33.25 ft. (10.13 m) to center. Record; S48-1/2E, 33.0 ft. (10.06 m).
the stump and base of a down lodge pole pine 9 ins. (23 cm) diam. scribed as recorded, brs S2W, 23.0 ft. (7.01 m) to center. Record; S2W, 23.76 ft. (7.24 m).
fir snag, 12 ins. (30 cm) diam., with healed single blaze brs N38-1/2W, 23.10 ft. (7.04 m) to center. Record; N38-1/2W, 22.44 ft. (6.84 m).

I mk the following trees CS BT and take measurements to center of trees at lower blaze:

lodge pole pine, 5 ins. (13 cm) diam., brs N40-1/2E, 18.0 ft. (5.49 m).
white pine, 10 ins. (25 cm) diam., brs S6W, 23.25 ft. (7.09 m).
lodge pole pine, 15 ins. (38 cm) diam., brs N52W, 40.80 ft. (12.44 m).

August 5, 1978

B. Malotte

R. Frost

Approved by: Ed McGinty
Co. Surveyor

FILED RECEIVED *zh*

NOV 20 1978

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

#3 - T30-4E ✓
#8 - T29-4E ✓

C. S. File No. 58/183-10