


TOWNSHIP 30 SOUTH
RANGE 4 EAST

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 1, Twp. 30 South, Range 3 East and Sec. 6,
Twp. 30 South, Range 4 East, W.M. $V=20-1/2^\circ$
Fd, projecting 4 ins. (10 cm), the original 1 in. (2.5 cm) diam. iron pipe
with standard G.L.O. brass cap mkd:



as recorded by H. Raymond in 1927.

Original bearing trees fd as follows:

sawed fir stump, 18 ins. (46 cm) diam., bears record S75E, 26.40 ft. (8.05 m)
to center.

white pine, 37 ins. (94 cm) diam., with healed single blaze, brs N15W, 12.8 ft
(3.90 m) to center. Record; N15W, 13.20 ft. (4.02 m)

I re-mark this tree CS BT and mk a new tree CS-BT:

white fir, 9 ins. (23 cm) diam., brs S55-3/4E, 16.1 ft. (4.91 m) to center
of tree at lower flaze.

Corner lies 66 ft. (20 cm) North of ridge top C. SE.

August 11, 1978
B. Malotte

Approved by: Ed McGinty
Co. Surveyor

#1 T 30-2E ✓
#1 T 30-3E ✓

FILED
RECEIVED *zh*

NOV 20 1978

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.