

TOWNSHIP 31 SOUTH
RANGE 2 EAST

FIRST RE-ESTABLISHMENT

Section corner common to Sec. 33, Twp. 30 South, Range 2 East, and
Sec. 3 and 4, Twp. 31 South, Range 2 East, W.M. V=20°
Fd, lying on top of the ground, a 2 X 38 ins. (5 X 97 cm.) iron pipe
with G.L.O. brass cap mkd:

T30S R2E
S33
S4|S3
T31S R2E
1937

as recorded by L. Carter.

I re-set this pipe (in the hole it originally occupied) 28 ins. (71 cm.)
in the ground, alongside the original 16 X 12 X 7 ins. (41 X 30 X 18 cm.)
record; 14 X 10 X 8 ins. (36 X 25 X 20 cm.) stone, mkd. with 3 grooves on
opposite sides.

Original bearing trees recorded by P. Applegate in 1891 and noted by
L. Carter in 1937, fd as follows:

The base of a tipped over fir, 30 ins. (76 cm.) diam., containing
scribed "T30" in partially axed out face brs as recorded by Carter; N32°E,
21.12 ft. (6.44 M.). He reports obliterating mks on this tree in 1937.

Sawed fir stump, 58 ins. (147 cm.) diam., brs , as recorded by Carter;
S7°E, 29.04 ft. (8.85 M.) to center.

shasta red fir, 46 ins. (117 cm.) diam., with healed blazes, brs record
(Carter): S41°W, 53.46 ft. (16.29 M.) to center of tree.

stump hole fd at record location of original NW BT.

The brass cap corner of sections 33 and 34 brs S87½°E, 82.73 ft. (25.22 M.).
Record; S88°49'E, 81.84 ft. (24.94 M.).

I mound stones around corner, and mk a new tree CS BT:

white fir, 29 ins. (74 cm.) diam., brs N26 3/4°W, 38.36 ft. (11.69 M.)
to center of tree at lower blaze.

Corner lies at NW edge of old skid road.

May 22, 1978
B. Malotte
R. Frost

Approved by: Ed McGinty
County Surveyor

#5 T 31-2E ✓

FILED
JACKSON CO.
TAN DOUG
SIDE

FILED
RECEIVED *vh*

NOV 20 1978

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.