

TOWNSHIP 31 SOUTH  
RANGE 2 EAST


*Douglas*

FIRST RE-ESTABLISHMENT

Section corner common to Secs, 4, 5, 8 and 9, Twp. 31 S., Range 2 East, W.M.  
V= 21 3/4°

From the following original evidence, at the location described below, I set a  
1 X 36 ins. (2.5 x 91cm) G. I. pipe, 35 ins. (89 cm) in the ground with a 2 1/2 ins.  
(6 cm.) bronze disc. mkd:

JACKSON COUNTY 1978  
T31S R2E



Original bearing trees recorded by P. Applegate in 1891 found as follows:

Fir stump, 52 ins. (132. cm.) diam. with healed blazes, brs. record; N 80 E,  
9.24 ft. (2.82m) to partially exposed upper face.

The stumphole of a tipped out fir stump, 40 ins. (102 cm.) diam., brs. record;  
S10E, 25.74 ft. (7.85 m)

Sawed fir stump, 32 ins. (81 cm) diam. scribed "BT" in opened lower face, brs.  
S66W, 46.20 ft. (14.08 m) to scribed face. Record; S66W, 40.26 ft. (12.37 m)

NW BT now gone and original stone not found.

I mark the following trees CS BT and take measurements to center of trees at lower  
blaze:

- Shasta red fir, 12 ins. (30 cm.) diam. brs. N70 1/2 E, 93.33 ft. (28.45 m)
- Shasta red fir, 11 ins. (28 cm.) diam; brs. S 33 E, 16.15 ft. (4.92 m)
- Shasta red fir, 13 ins. (33 cm.) diam; brs. S50W, 119.20 ft. (36.33 m)
- Shasta red fir, 20 ins. (51 cm.) diam., brs. S 88 1/2 W, 135.03 ft. (41.16 m)

Note: no suitable tree in NW quadrant.

Corner lies about 40 ft. (12 m) south and 60 ft. (18 m) East of old skid road  
in clear cut, an estimated 200 ft. (61 m.) south of N. edge. and 400 ft. (122 m.)  
West of East edge of clear cut.

June 27, 1978  
B. Malotte  
R. Frost

Approved by: Ed McGinty  
Co. Surveyor

#2 ✓

FILED  
RECEIVED *JK*

NOV 20 1978

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.