

TOWNSHIP 31 SOUTH  
RANGE 2 EAST

Douglas

FIRST RE-ESTABLISHMENT

Section corner common to Secs. 4 and 5, Twp. 31-South, Range 2 East, W.M.  
V=17°

Fd, firmly set, exposed 15 ins. (38 cm) in mound of stone, the 2 ins. (5 cm) diam. iron pipe with G.L.O. brass cap mkd:

T30S R2E  
32  
S5 | S4  
T31S R2E  
1937

FILED  
RECEIVED *UH*

NOV 20 1978

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

as recorded by L. Carter in 1937

Original bearing trees recorded by P. Applegate in 1891 and noted by Carter fd as follows:

fir snag, 50 ins. (127 cm) diam., brs N30E, 31.67 ft. (9.65 m) to center. Record; N30E, 29.04 ft. (8.85 m).

fir snag, 11 ins. (28 cm) diam., with upper blaze axed out, brs N37W 46.7 ft. (14.23 m) to center. Record; N37W, 44.88 ft. (13.68 m).

NOTE: Carter notes obliterating mks on the above trees in 1937.

shasta red fir, 37 ins. (94 cm) diam., with healed blazes, brs S30E, 7.50 ft. (2.29 m) to center. Record; S23E, 7.26 ft. (2.21 m)

white fir, 26 ins. (66 cm) diam., with healed blazes, brs S5W, 14.00 ft. (4.27 m) to center. Record; S5W, 14.52 ft. (4.43 m).

I mk a new tree CS BT:  
shasta red fir, 20 ins (51 cm) diam., brs N82W, 42.00 ft. (12.80 m) to center of tree at lower blaze.

June 12, 1978  
B. Malotte  
R. Frost

Approved: Ed McGinty  
Co. Surveyor

#3 T31-2E ✓

FIRST RE-ESTABLISHMENT

Quarter corner common to Sec. 4, Twp. 31 South, Range 2 East, W.M.  
V=19 1/2°

Fd, bent over, the 1 in. (2.5 cm) diam. iron pipe with G.L.O. brasscap mkd:

1/4 S4  
1937

as recorded by L. Carter in 1937.

I removed, straighted and re-set said pipe in the original hole, (now projects 10 ins. - 25 cm), from which:

the center of fir stump remains of original bearing tree recorded by P. Applegate in 1891 and noted by Carter brs record; S50E, 11.22 ft. (3.42 m).

Bearing trees mkd by Carter fd as follows:

sawed shasta red fir stump, 36 ins. (91 cm) diam. with healed blaze, brs S30E 55.40 ft. (16.89 m) to center. Record; S30E, 56.10 ft. (17.10 m).

sawed shasta red fir stump, 40 ins. (102 cm) diam, brs S1W, 52.20 ft. (15.91 m) to center. Record; S1W, 50.82 ft. (15.49 m).

I mk new trees CS BT and take measurements to center of trees at lower blaze:

shasta red fir, 12 ins. (30 cm) diam., brs S38W, 28.80 ft. (8.78 m)  
hemlock, 16 ins. (41 cm) diam; brs N25W, 30.70 ft. (9.36 m)

Corner lies about 350 ft. (107 m) East of location marker on 36 ins. (91 cm) diam., shasta red fir, located alongside road, C. N-S.

June 12, 1978  
B. Malotte  
R. Frost

Approved by: Ed McGinty  
Co. Surveyor

#A ✓