

LICENSED IN  
OREGON  
WASHINGTON  
CALIFORNIA

1781-28

**T. FLATEBO AND ASSOCIATES, INC.**  
CIVIL ENGINEERS AND LAND SURVEYORS  
(503) 899-8267  
P. O. Box 900  
937 NORTH FIFTH STREET  
JACKSONVILLE, OREGON 97530

TORLEIV FLATEBO, P. E.  
899-9000  
KURT C. WEAVER, P. L. S.  
899-7845  
DANIEL R. FRANK, R. S.  
855-7593

April 6, 1981

FILED  
RECEIVED  
APR 7 1981  
COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE

Ms. Virginia Laugen  
Douglas County Surveyors Office  
Room 205, Justice Building  
Roseburg, OR 97470

Reference: Bearing Trees for Corners in Section 6,  
T.31S., R.1W., W.M.

Dear Virginia:

I have been out of town extensively in the past two months and have been incapable of responding to your letter, and I apologize for the delay.

The following corrections to the referenced bearing trees should rectify the problem:

CN 1/16: Willow snag 3" dia. bears S17°01'E 50.5 feet  
(record S15°E 50.7 feet)  
Willow 4" dia. bears S32°45'W 68.7 feet  
(record S34°30'W 68.7 feet)  
Set 5/8"x30" iron bears N54°01'W 27.4 feet

S 1/16 1/6: W. Oak 10" dia. bears S9°44'W 35.3 feet  
(record S12°W 35.1 feet)  
W. Oak 8" dia. bears N24°14'W 32.3 feet  
(record N21°30'W 32.3 feet)

1/4 6: D. Fir 21" dia. bears S44°46'E 22.5 feet  
7 (record S45°15'E 22.5 feet)  
D. Fir 17" dia. bears N24°15'E 19.2 feet  
(record N23°45'E 19.3 feet)

Thank you for bringing this matter to my attention.

Sincerely,



Kurt C. Weaver  
Professional Land Surveyor

KCW/ssdr

Survey No. \_\_\_\_\_

M 81-28

FILED  
RECEIVED

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250.

NOV 29 1979

Survey For: Umpqua National Forest  
P.O. Box 1008  
Roseburg, Oregon 97470

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

Location: Located in the Northeast and the Southwest  
Quarters of Section 6, Township 31 South,  
Range 1 West of the Willamette Meridian,  
Douglas County, Oregon.

Purpose: To monument the E 1/16 corner of Sections  
31 and 6 as well as the NE 1/16 and the  
SW 1/16 of Section 6. Also to mark the  
North, South and East lines of the North-  
west quarter of the Northeast quarter of  
Section 6 with posts and "Forest Boundary"  
signs. As well as to mark the North and  
East lines of the Southwest quarter of the  
Southwest quarter of Section 6 with post,  
"Forest Boundary" signs and blazed trees.

Procedure: Utilizing a series of closed traverses I  
tied the controlling corners shown on the  
accompanying map. This was done with a  
Wild T-2 theodolite and an H.P. 3805 A  
E.D.M. The previous subdivision of Section  
6 was analyzed and the monuments were  
determined to be in acceptable position.

Monuments were set as shown on the  
accompanying map.

Bearing was based on a solar observation.

Surveyed By: T. Flatebo and Associates, Inc.  
P.O. Box 900  
Jacksonville, Oregon 97530

Date: Survey began October 22, 1979 and was  
completed November 9, 1979.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Kurt C. Weaver*

OREGON  
JULY 14, 1978  
KURT C. WEAVER  
1679

58/216-5b

M 81-28