

FILED

RECEIVED JHH

DEC 4 1979

Re: 133-79
Grady Robinson

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

M 81 - 32
N A R R A T I V E

I, found the monuments along the easterly R/W line of State Hwy 42, that were set and/or found per M73-45; I, used $S35^{\circ}06'39''W$, per M73-45, as the Basis of Bearings of this survey.

I, found and traversed thru and tied additional monuments as found per surveys noted on the attached map. Using the location of the West line of survey M28-13, I projected the West line Southerly 70.00 feet from the $\frac{1}{2}$ " iron pipe, at the NE corner of Lot 2 Block 2, Winston View Home Sites, I then inversed to the monuments on the South line of survey M28-13, from the SE cor of Lot 2 Block 2; therefore, establishing the North line of subject property being surveyed. I then produced the North line westerly 110.00 feet (call distance), to establish the SW corner of said Lot 2 Block 2, this corner also being the NW corner of the property being surveyed. I then inversed to a found $\frac{3}{4}$ " iron pipe, as noted per survey M77-54. I then calculated the SW corner of subject property, using the call distance of 151.8 feet, as shown on the plat of Winston View Home Sites. From the SW corner I inversed to a $\frac{5}{8}$ " iron rod, as shown on survey M77-54, this proved to be the best location of the South line of subject property. I then produced the South line Easterly and intersected the Westerly R/W line of State Hwy 42 and set the SE corner of subject property. To establish the NE corner, I used the $\frac{1}{2}$ " iron pipes, shown on survey M28-54 and produced the line easterly to its intersection with the Westerly R/W line of State Hwy 42. All other property corners are as shown on my survey map.

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
MAY 13, 1960
EUGENE A. BLOOM
492

EUGENE A. BLOOM
Registered Land Surveyor
No. 492

C. S. File No. CS 58/217-1

MAP FILE M 81 - 32