

M 79-47

MINOR AND MAJOR LAND PARTITIONS  
SUBDIVISIONS - CADASTRALS - SLOPE STAKING  
PROPERTY AND LOT SURVEYS - ALTA'S

FILED  
PHONE 1-503-678-2096  
RECEIVED *jjf*

JUL 28 1980

# AA SURVEYING SERVICE INC COUNTY SURVEYOR

2498 OLD HWY. 99 S.  
July 28, 1980

DOUGLAS COUNTY, ORE.  
ROSEBURG, OREGON 97470

P.O. Box 454

163-80FB53-58  
Sec. 16, T.30S. R.7W.W.M.

## N A R R A T I V E

The objective in Surveying Section 16, T.30S. R.7W.W.M., is to set the one-sixteenth corners on the North, South and West lines; also, to mark and blaze said lines.

The field crew consisted of: Darrell R. Jones, Marc Holt, Donald L. Bloom, Richard Hanson, and Eugene A. Bloom.

The Instruments used were: Lietz TM-6 Theodolite, K & E Auto Ranger EDM and steel chain.

The Traverse was run from the Southeast corner of Section 16 West, North, East and then South to the Beginning Point, tying in all of the known corners on the respective lines to be Surveyed.

The North one-quarter corner has not been renewed, before or after, the Witness Corner was set. The North one-quarter corner appears to be out of position East & West. We made a search for other BT.'S, other than the ones showing on the annexed map. However, most of the trees along the North line have been logged.

The Basis of Bearings for this Survey is the East half of the South line, based on the original G.L.O. Bearing.

The Angular Error of Closure was: 0°00'00.8" per Angle.

The Perimeter Closure was: 1 ft. in 29,227 feet.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Eugene A. Bloom*  
OREGON  
MAY 13, 1960  
EUGENE A. BLOOM  
492

C & File No. 58/217(N) <sup>4</sup>