

DOUGLAS COUNTY

During a recent survey in Section 6, Township 31 South, Range 9 West, Willamette Meridian. I found and remarked the following corners.

I set a 5/8" rod for the Corner C.S. 1/16 Corner in Section 6 from a 24" fir B.T. with scribes plain bearing S41° 40'W 29.5 feet (this tree is now a 26" snag). I scribe "1/16 S B.T. 378" on a 20" fir N24° 45'E 43.9 feet. I also set a metal fence post 0.4 feet South of the corner rod.

I find a squared stake in place at the center of Section 6. The 46" fir B.T. N36° W 74.1 feet is now a stump with plain scribes and the 36" fir B.T. S71°E 59.6 feet is now a stump with plain scribes. I scribe "C 1/4 S 6 B.T. 378" on a 10" Hemlock N22° 30'E 18.3 feet and "C 1/4 S 6 B.T." on a 10" Hemlock S14° 00'W 21.7 feet. I also set a 5/8" rod by the squared stake at the corner.

I find a 1" 1967 brass cap pipe at the 1/4 Corner between Sections 6 and 7 with the stump of the original 36" fir B.T. S09° E 22 links and the stump of the original 30" fir N12° E 25 links with the face grown over. I also find a 15" fir B.T. S37° 00'W 42.3 feet with face grown over.

Jack E. LaFlamme

Jack E. LaFlamme
R.O.L.S. # 378

(GEORGIA-PACIFIC)

November 20, 1980

FILED

RECEIVED *JL*

NOV 24 1980

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

c 1/4 # 162 ✓

58/249-1
C. S. File No. *58/248* C