

FILED ✓
RECEIVED BS

AUG 5 1983

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

VEL AND JOHN KOOPMANS

August, 1983

See accompanying Map M 94-57

NARRATIVE:

PURPOSE: To set the NW 1/16 corner of section 2,
T. 29 S., R. 7 W., W.M.

FINDINGS: The north portion of section 2 has been
lotted. The NW corner of the section is
perpetuated from original evidence. The
N 1/4 corner was re-established at prop-
ortionate distance by A. Boyer in 1941.
The W 1/4 corner was re-established and
the N 1/16 corner established at propor-
tionate distances by G. Baughman in 1980
(M85-35) and were checked by a B.L.M.
resurvey in 1981. The section was sub-
divided and the center 1/4 corner set by
R. Kimberly in 1982 (M90-18). I set the
center west 1/16 corner in 1983 (CS 58/
182)

CONCLUSIONS AND PROCEDURE:

I accepted the corners described above.
I calculated the position of the center
north 1/16 corner at proportion distance.
I then established the position of the
NW 1/16 corner and set a monument as
shown.

EQUIPMENT: Topcon GTS-2.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Herman A. Pieske

OREGON
JULY 14, 1978
HERMAN A. PIESKE
1651

AA SURVEYING SERVICE, INC.
P.O. Box 130,
Roseburg, OR 97470
(503) 672-2096

C. L. File No. 58/263³(u)