

M 96-55

FILED *AS*  
RECEIVED *BS*

MAY 16 1984

NARRATIVE OF SURVEY  
FOR: RICHARD KILDUFF  
BY: AA SURVEYING SERVICE, INC.  
P.O. BOX 130  
ROSEBURG, OREGON  
MAY 1984

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

LOCATION: Part of the E $\frac{1}{2}$ W $\frac{1}{2}$  Section 15 Township 27 South, Range 7  
West W.M. Douglas County, Oregon.

PURPOSE: To monument and mark boundary lines of that land described  
in Book 794, page 846, Douglas County Deed Records.

PROCEDURE: I found all existing corner evidence and monuments as shown on  
my map. Certain corners fall in the county road and have  
been perpetuated by the county surveyor's office with witness  
corners. The following is a description of the evidence which  
I used to determine the true position for these corners.

No. 1 NW Corner of Section 15

- An Original 15" W. Oak, now 24" , N. 20° 11' E., 55.4 Ft. dist. (N.20°E., 55.4 Ft. Dist.) with visible scribe "W C O"
- A 15" D. Fir, now 23", S. 61° 33' E., 125.5 Ft. dist. (S. 61° E., 125.5 Ft. dist.) with healed blaze (CS Ren. 81)

No. 2 1/4 Corner to Sections 10 and 15

- An Original 16" W. Oak, now 26", N.02° 18' E., 38.9 Ft. dist. (N. 6° E., 38.9 Ft. dist.)with well healed blaze.
- An Original 24" W. Oak, now 33", S. 32° 13' E., 84.5 Ft. dist. (S. 32° E., 84.5 Ft. dist.) with well healed blaze.

No. 11 SW Corner of Section 15

- A 10" B. Oak, now 11" W. Oak, N. 21° 29' W., 85.8 Ft. dist. (N.17° 30' W., 85.8 Ft. dist.) with healed blaze. (CS Ren. 54)
- A 1½" iron pipe with 2¼" brass cap set by Douglas County Surveyor in 1954 N.89° 49' W., 32.0 Ft. dist. ( West, 32.0 Ft. dist.) marked "County Surveyor's Office  
T 27 S R 7 W  
W.C.  
S16 | S15  
S21 | S22  
32' to East  
1954

I used a random close traverse method to tie all existing corners and along the perimeter of the subject property.

M 96-55

NARRATIVE OF SURVEY  
FOR: RICHARD KILDUFF  
BY: AA SURVEYING SERVICE, INC.  
CONT.

FILED  
RECEIVED *BS*

MAY 16 1984

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

I subdivided Section 15 per the BLM 1973 Manual of Surveying Instruction. I monumented the corners of the subject property as shown, and flagged the lines.

EQUIPMENT: Topcon GTS-10

PERSONNEL: Ron Quimby, PLS  
Karen Reed  
Gene Bloom, PLS  
Dave Stringer, PLS  
Darrel Jones  
Dave Orlandi  
Ron Gilbert

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*  
OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654