

HARD TIMES LODGE

MINERAL SURVEY #920

①

T335 R5W S12

FD: A BASALT STONE 20" x 12" x 8",
 4 INS. IN GROUND (RECORD
 24" x 14" x 8", 16 INS. IN GROUND)
 MARKET " HT 3-920 "

A 28" D. FIR (NOW 34") BEARS
 S. 35° W., 55.5 FT. DIST (RECORD
 S. 38° W.) NO BLAZE

A 16 IN. SUGAR PINE (NOW 24 IN.)
 BEARS S. 85° W., 23.4 FT DIST.
 (RECORD S. 89½° W., 24.6 FT DIST.)
 NO BLAZE.

THE TWO ABOVE TREES HAVE
 NO APPARENT BLAZE OR
 SCRIBING AS CALLED FOR IN
 THE RECORD HT 3 920 BT "

SET: A 1" x 30" GAL. IRON PIPE
 WITH BRASS CAP 25" IN
 GROUND MARKED:

COR # 3

10-18-76

HARD TIMES LUPE

(2)

MINERAL SURVEY #920

T33S R5W S12

DOUGLAS CO. SURVEYOR

T33S R5W

COR.

3

MS

920

1976

SET MARKED PORTION OF
STONE 16" X 10" X 6" ON
EAST SIDE CAP. (STONE
BROKE IN HALF)

SET BRASS CAP AT ORIG.
STONE'S LOCATION. DUE
TO DISCREPANCY IN THE
BEARINGS AND DIST. IN
THE FOUND BTS., CALLS
FROM RAVINE (COURSE
S. 70° W., 100 FT) A TRAIL
(COURSE S. 72° W., 7 FT)
AND A LOCATION MARKER

DIETZEN NO. 3855-6

C. S. File No. 59/2A

34

COR # 3

10-18-76

HARD TINES LOOSE

(3)

MINERAL SUCUBY #920

A 12" FIR STUMP 40 IN.
HIGH WITH UPPER MOST
2 1/2 FT CUT WITH AXE
8 IN SQUARE, BEARING
S. 11° 47' E., 2.6 FT DIST
FROM CORNER ARE
USED FOR EVIDENCE
TO SHOW STAKE AT
TRUE LOCATION.

NEW BTS

A 16 IN D. FIR BEARS
S. 88° E., 29.6 FT. DIST.

DOUBLE BLADED HAND

SCRIBED "HT 3 920 CS BT"

A 16 IN SUGAR PINE BEARS

N. 62° E., 56.8 FT DIST

DOUBLE BLADED HAND SCRIBED

"HT 3 920 CS BT"

C. S. File No. 59/24

CUR #3

10-18-76

HARD TIMES LODGE

(4)

MINERAL SURVEY #920

DECLINATION

20° EAST

K. CHENEY

G. LANGLITZ

OK
JAL

DIETZGEN NO. 385-6

C. S. File No. 59/24

34