

11-2-76

$\frac{1}{4} \frac{28}{33}$ T22S R7W

(SEE REN. #143)

FOUND:

BOTH BEARING TREES AS NOTED BY HAINES
IN REN. #143 AS FOLLOWS:

AN 8" NOW 16" D FIR, ALIVE AND WELL WITH
HEALED DOUBLE BLAZE,

AND A 54" D. FIR STUMP WITH BRIDGE SPIKE
DRIVEN IN THE CENTER.

WE DO NOT FIND THE "T" IRON SET BY
HAINES.

AT THE CORNER POINT AS DETERMINED BY
THE RECORD MEASUREMENTS TO THE ABOVE
MENTIONED BEARING TREES:

A 16" D. FIR BEARS $N23\frac{1}{2}^{\circ}E$ 10⁰ FT.,

AND A BRIDGE SPIKE IN A 54" D. FIR STUMP
BEARS $S18^{\circ}E$ 13⁰ FT.,

#175 ✓

U. S. File No. 59/26 PAGE 1 C

NEW SW BT

7" DFR

S 51° W 59 LVL

1/4 S 33 CS BT

~~5/8" J 200~~

3³⁵ LVL S 47° E

WE SET A 1" X 30" IRON PIPE, 26" IN THE GROUND WITH BRASS CAP ATTACHED:

MARKED:

DOUGLAS CO. SURVEYOR

T22S R7W

$\frac{1}{4}$ S28
S33

1976

WE MARK AN ADDITIONAL BEARING TREE AS FOLLOWS:

A 7" D. FIR BEARS S 51° W 5 $\frac{1}{2}$ FT.,
SCRIBED " $\frac{1}{4}$ S33 CS BT" ON A DOUBLE
PLATE.

A $\frac{5}{8}$ " IRON ROD BEARS S 47° E 3 $\frac{3}{4}$ FT.

OUR RECORDS INDICATE A $\frac{5}{8}$ " I ROD AS
BEING FOUND AT THE $\frac{1}{4}$ CORNER IN 1974,
(SEE M 53-42A), BUT NO INDICATION IS
MADE CONCERNING WHEN THE $\frac{5}{8}$ " I ROD WAS
SET.

NOTE: THIS CORNER IS LOCATED APPROX 100 FT.,
N 20° W OF A CASCADE UTILITIES TRANSMITTER
SITE.

COMPASS DECL. SETTING:
20° EAST

11-2-76
Lauri Langley
KAREN CHENEY

OK
[Signature]

DIETZSEN NO. 385-6

C.S. File No. 59/20