

DATE: 2-16-78

SURVEYOR'S
T26S R1W

OFFICE

S10 | S11
S15 | S14

W
T
N
C
O
O

1978

Condition Report Only
 Not Found
 Renewed
 Unrecorded
 Surveyed In
 Referenced Out

Previous Renewal #'s _____

Monument(s) Found: (Condition and Source) ORIGINAL CORNER

STONE FIRMLY SET IN THE GROUND.

STONE MEASURES 18" x 9" x 7" & IS

MARKED "X" ON TOP & HAS 4 NOTCHES

ON THE SOUTH EDGE AND 2 NOTCHES

ON THE EAST EDGE.

ACCESSORY FOUND: ORIGINAL B.T. TO

THE S.W. IS DOWN & DECAYED. STUMP
HOLE BEARS S87°W, 9.24'

Accessories Found: (Condition and Source) ORIGINAL 38", NOW

37" DOUG FIR SNAG BEARS N65°W, 54.8' (RECORD N63°W)

AXE MARKS ON BARK WHERE BLAZE WAS.

ORIGINAL 24", NOW DECAYED FIR SNAG BEARS

S27°E, 14.48' (RECORD S24°E, 15.18') HAS

AXE MARKS ON BARK WHERE BLAZE WAS.

~~IF~~ ORIGINAL 24", NOW DECAYED DOUG

FIR SNAG BEARS N87°E, 16.5'

AXE MARKS ON BARK WHERE BLAZE WAS

CS Page 1 of 1 C
No. 52/46-19

NEW ACCESSORY:

A 30" DOUG FIR BEARS N 79° 30' E,
40.1' SCRIBED "T265 RIW S11CS BT"
ON A DOUBLE BLAZE. PLACED
COUNTY B.T. SIGNS ON ALL B.T.'S

RENEWAL

Monument Set: (Procedure and Description) MOVING THE
CORNER STONE ASIDE, I SET IN ITS PLACE
A 2 1/2" BRASS CAP ON A 1" IRON PIPE,
BRASS CAP STAMPED AS SHOWN ON REVERSE,
I BURY THE CORNER STONE ALONGSIDE.

New Accessories: (Description) A 26" DOUG FIR BEARS
N 64° W, 41.0' SCRIBED "T265 RIW S10CS BT" ON DBL. BLAZE
A 21" DOUG FIR BEARS S 70° W, 7.3' SCRIBED
"T265 RIW S15CS BT" ON A DOUBLE BLAZE,
A 16" DOUG FIR BEARS S 9° E, 24.2' SCRIBED
"T265 RIW S14CS BT" ON A DOUBLE BLAZE.

Location and Comments:	<u>20° E</u>	Compass Declination
	<u>U.S. F.S.</u>	Agency
	<u>DENNIS GAYLORD</u>	Party Chief
	<u>" "</u>	Notekeeper
	<u>RANDAL LOPEZ</u>	Witnesses
	<u>JIM TALBURT</u>	