

T265

DATE: 7-20-78

R3W

24

19

R2W

$\frac{1}{4}$

Condition Report Only

Not Found

Renewed

Unrecorded

Surveyed In

Referenced Out

#21 T26-2

Previous Renewal #'s 58, 92, 1855 AND 1910 GOVERNMENT SURVEYS

Monument(s) Found: (Condition and Source) NO TRACE OF ORIGINAL 1855  
OR 1910 CORNER POSTS.

Accessories Found: (Condition and Source) NO TRACE OF ORIGINAL 1855

BEARING TREES. FROM 1910 RETRACEMENT, WE FIND,

A 10" NOW <sup>13</sup>~~15~~" LAUREL (MADRONE) <sup>ALIVE</sup> WITH FRAGMENTARY REVERSE

SCRIBING FOUND ON UNHEALED BLAZE, BEARS ~~X~~ N 69°E 8<sup>6</sup> FT.

AND A 10" NOW 15" LAUREL (MADRONE), ALIVE, WITH WELL-HEALED

BLAZE WHICH WE OPEN AND FIND GOOD FACE BUT NO SCRIBING,

BEARS S 24°W 6<sup>6</sup> FT. (REL. S 21°W 6<sup>6</sup> FT.)

#223 T26-34

#113 T26-2 ✓

C. S. File No. 60/11-30

Page 1 of 2

C

RENEWAL

Monument Set: (Procedure and Description) AT A LOCATION WHICH AGREES  
WITH MEASUREMENTS SHOWN TO THE PREVIOUSLY DESCRIBED RESURVEY  
BEARING TREES, WE SET A 1" x 30" IRON PIPE, 27" IN THE GROUND,  
WITH BRASS CAP ATTACHED, MARKED: DOUGLAS COUNTY SURVEYOR

T 265

New Accessories: (Description)

S 24 | S 19  
R 3W | 1/4 | R 2W  
1978

WE MARK NEW BEARING TREES AS FOLLOWS:

A 32" D. FIR, SCRIBED "1/4 S 19 CS BT" ON A DOUBLE BLAZE,  
BEARS S 52° E 16<sup>2</sup> FT.

AND A 16" D. FIR, SCRIBED "1/4 S 24 CS BT" ON A DOUBLE BLAZE,  
BEARS S 71° W 33<sup>6</sup> FT..

Location and Comments: 20° EAST Compass Declination

(CONTINUED ON  
PAGE 2)

DOUGLAS COUNTY SURVEYOR Agency  
GARY L. LANGRISH Party Chief  
Gary L. Langrish Notekeeper  
FRANK C. SILAGY Witnesses  
GLEN MCCHESENEY, WEYERHAEUSER TIMBER CO.

OK *[Signature]*

DATE: 7-20-78

T265

R3W 24 / 19 R2W

$\frac{1}{4}$

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

(CONTINUED) SEE "NEW ACCESSORIES"

Previous Renewal #'s \_\_\_\_\_

Monument(s) Found: (Condition and Source) \_\_\_\_\_

Accessories Found: (Condition and Source) \_\_\_\_\_

RENEWAL

Monument Set: (Procedure and Description) \_\_\_\_\_

New Accessories: (Description) OUR NEW SE BEARING TREE,  
A 32" D. Fir, WAS PREVIOUSLY USED AS A REFERENCE POINT BY  
WEYERHAEUSER (REN. # 58 & 92), NEW MEASUREMENTS TO "W"-  
NAIL S 53 1/2° E 15 3/4 FT.

WE SEARCH FOR EVIDENCE IN A 20" HEMLOCK STUMP BEARING S 38° W  
8 1/2 FT. ON THE SUSPICION THAT THIS MAY BE THE ORIGINAL 1855 SW BEARING  
TREE, A "15" SPRUCE". NO EVIDENCE FOUND. THIS STUMP WAS USED BY WEYERHAEUSER

<del>Location and Comments:</del>	_____	Compass Declination
TO REFERENCE THIS CORNER,	_____	Agency
(REN. 58 & 92). WE REMOVE	_____	Party Chief
THE "W-NAIL" IN THE COURSE	_____	Notekeeper
OF OUR SEARCH.	_____	Witnesses
	_____	
	_____	