

DATE: Sept 20, 1979

COUNTY SURVEYOR'S OFFICE
T315 1/4 R3W
532 | 533
1979

Condition Report Only
 Not Found
 Renewed
 Unrecorded
 Surveyed In
 Referenced Out

Previous Renewal #'s 165

Monument(s) Found: (Condition and Source) BRASS CAPPED
IRON PIPE SET BY COUNTY SURVEYOR'S OFFICE
IN 1966 IS FIRMLY SET IN PLACE & MARKED:
COUNTY SURVEYORS OFFICE
T315 R3W
1/4 532 | 533
1966

THIS BRASS CAP WAS ERRONEOUSLY SET.
RECORD BEARING FROM THE ORIGINAL
(CONTINUED ON PAGE 2)

Accessories Found: (Condition and Source) _____
ORIGINAL 10" FIR, NOW 18", IS DOWN &
DECAYED. PREVIOUSLY OPENED FACE
SHOWS SCRIBING "S" ON UPPER BLAZE
& FRAGMENTARY SCRIBING ON LOWER
BLAZE. ROOT HOLE FOR THIS B.T.
IS EASILY IDENTIFIABLE & BEARS N80°E,

#206 X

26.4 FT. FROM THE CORNER POINT,

A DEPRESSION SURROUNDED BY FIR ROOTS

BEARS $S62^{\circ}W$, 18.48 FT. NOTHING

ELSE REMAINS OF THE SW BT.

(CONTINUED ON Pg. 2.)

RENEWAL

Monument Set: (Procedure and Description) SET A 1" IRON

PIPE WITH A 2 1/2" BRASS CAP, MARKED AS

SHOWN ON REVERSE, BY REFERENCE FROM

THE ABOVE DESCRIBED ORIGINAL B.T.

EVIDENCE. I REMOVE ALL MARKS FROM

1966 BRASS CAP & LEAVE IT IN PLACE.

New Accessories: (Description)

A 13" DOUGLAS FIR BEARS $N7^{\circ}W$,

10.7 FT. SCRIBED "1/4 S32 CS BT"

ON DOUBLE BLAZES.

Location and Comments:

20° E

Compass Declination

U.S. F.S.

Agency

DENNIS GAYLORD

Party Chief

"

"

Notekeeper

TONY FLORES

Witnesses

OK [signature]

DATE: _____

____ Condition Report Only
____ Not Found
____ Renewed
____ Unrecorded
____ Surveyed In
____ Referenced Out

Previous Renewal #'s _____

Monument(s) Found: (Condition and Source) REMAINING

B.T. IS N80°E. THIS 1966 BRASS
CAP WAS SET S8°W FROM THE B.T.

Accessories Found: (Condition and Source) A 14" DOUG. FIR

WITH DOUBLE HEALED BLAZES WHICH FACE
THE TRUE CORNER LOCATION BEARS S39°E,
44.9 FT.

A 10" DOUG. FIR BEARS S21°E, 32.6 FT.
& HAS DOUBLE HEALED BLAZES. THE
BLAZES ON THIS TREE DO NOT FACE

THE TRUE CORNER LOCATION. THESE
LAST TWO B.I.T'S WERE SET BY
THE COUNTY SURVEYOR IN 1966.

RENEWAL

Monument Set: (Procedure and Description) _____

New Accessories: (Description) _____

Location and Comments:	_____	Compass Declination
	_____	Agency
	_____	Party Chief
	_____	Notekeeper
	_____	Witnesses

Willamette Meridian.

Chain North between Sections 32. and 33 Variation 20° E

34. Top of ridge C & W 900

40. Set 1/4 Sec post from which 100

A Fir 10 in diam bear A 80° E dist 40 lks

" " 16 " " " S 62° W " 28 "

61. A Gulch with water C W. 00

80. Set post in dry gulch corner to Sections 28, 29, 32 and 33. from which 100

A Fir 16 in diam bear A 38° E dist 37 lks

" " 16 " " " S 60° E " 31 "

" " 10 " " " S 30° W " 22 "

" " 14 " " " A 50° W " 35 "

Land and Timber 2d rate. Principally Fir and Pine Timber.

Cast on a random line between Sections 28 and 33. Pa 20° E

40. Set 1/4 Sec post

80. Intersect at post corner to Sections 27, 28, 33, and 34. from whence