

DATE: OCT. 8, 1981

T325 R34  
CNTR. 1/4  
COR. • S14  
ORE. LIC. 544  
1971

Condition Report Only  
 Not Found  
 Renewed  
 Unrecorded  
 Surveyed In  
 Referenced Out

Previous Renewal #'s 152

Monument(s) Found: (Condition and Source) \_\_\_\_\_

2" IP, FIRMLY SET, PROJECTING 6" ABOVE GROUND,  
WITH BRASS CAP MARKED AS ABOVE, SET BY  
DON GARRETT, OREGON LAND SURVEYOR #544,  
IN 1971.

Accessories Found: (Condition and Source) \_\_\_\_\_

BT'S MARKED BY GARRETT IN 1971:

A 10" HEMLOCK, S80°E, 19" FT. (REC.: W. FIR,  
S80°W), WITH SCRIBE MARKS "C 1/4 S14 BT" VISIBLE  
ON PARTIALLY HEALED BLAZE.

A 12" HEMLOCK, S62 1/2°W, 8 1/2 FT. (REC.: W. FIR),  
WITH SCRIBE MARKS "C 1/4 S14 BT" VISIBLE ON

#206 ✓

G. S. File No. 61/29-7 Page 1 of 1

PARTIALLY HEALED BLAZE.

RENEWAL

Monument Set: (Procedure and Description) \_\_\_\_\_

New Accessories: (Description) \_\_\_\_\_

Location and Comments: 19 1/2° E Compass Declination

U.S.F.S. Agency

LEONARD HERZSTEIN Party Chief

Notekeeper

CORNER IS ON  
STEEP NORTH SLOPE JIM LANDRUM

Witnesses

AT SOUTHERN JERRY PIEACE

EDGE OF CLEAR-CUT \_\_\_\_\_

OK  
JLM