

T 29 S R 1 E

DATE: OCTOBER 14, 1981

1/4 S 18 | S 17

Condition Report Only
 Not Found
 Renewed
 Unrecorded
 Surveyed In
 Referenced Out

Previous Renewal #'s NONE

Monument(s) Found: (Condition and Source) 1921 MONUMENT A 1" X 36"

IRON PIPE BURIED WITH 30 INCHES ABOVE GROUND, ATTACHED BRASS CAP IS
" 1/4 "
STAMPED S 18 | S 17 .
1921

Accessories Found: (Condition and Source) WE DID NOT LOCATE ANY

EVIDENCE OF THE TWO ORIGINAL BEARING TREES. AS WE ARE
UNSURE OF MONUMENT POSITION AS LOCATION OF ORIGINAL
QUARTER CORNER POSITION, WE CHECK THE FOLLOWING

COLLATERAL CALL EVIDENCE.

1) SOUTH 184^B FEET RIGHT BANK OF RIVER (REC) THIS BEARING AND
DISTANCE FALLS ON RIGHT SHORE AREA OF SOUTH UMPQUA RIVER.

#188 ✓

2) SOUTH 99 FEET TRAIL COURSE E AND W (REC). THIS BEARING
AND DISTANCE FALLS SHORT OF PRESENTLY TRAVELED ROADWAY DITCH
APROX. 5 FEET.

3) NORTH 33 FEET CREEK BED COURSE SE (REC) THIS BEARING AND DISTANCE
FALLS IN CURRENT CREEK BED, CONSIDERABLE EROSION IN THIS AREA
MAKES IT IMPOSSIBLE TO DETERMINE 1921 CREEK BED LOCATION.

RENEWAL

Monument Set: (Procedure and Description) AT POSITION OF

TO PERPETUATE POSITION OF FOUND MONUMENT AS EVIDENCE OF

QUARTER CORNER LOCATION WE BURY A 1" X 30" IRON PIPE, WITH ATTACHED

BRASS CAP, 24 INCHES INTO GROUND. CAP IS STAMPED
DOUGLAS COUNTY SURVEYOR
T 29 S R 1 E

1/4 S18/S17
1981

WITH MOUND OF STONES AROUND.

New Accessories: (Description) _____

1) A FIR 18" DIA DOUBLE BLAZED AND SCRIBED "1/4 S18 CS BT" BEARS N 26 1/2° W 16 1/2 FEET.

2) A FIR 8" DIA DOUBLE BLAZED AND SCRIBED "1/4 S18 CS BT" BEARS S 64 1/2° W 36° FEET.

3) A FIR 9" DIA DOUBLE BLAZED AND SCRIBED "1/4 S17 CS BT" BEARS S 12° E 27 8 FEET

4) AN ASH 10" DIA DOUBLE BLAZED AND SCRIBED "1/4 S17 CS BT" BEARS N 29° E 22 5 FEET.

Location and Comments: 19° EAST. Compass Declination

DOUGLAS Co. SURV. OFF. Agency

LARRY E. MOURBAN DEPUTY Party Chief

Larry E. Mourban Notekeeper

T.R. PLOUFF Witnesses

