

GOVERNMENT CORNER RESTORATION FORM

Township 21 S Range 10 W Sec. 1, 12 County DOUGLAS

State OREGON Date 1-13-82 No. \_\_\_\_\_

Corner Designation

1  
12

- \_\_\_\_\_ Condition Report Only
- \_\_\_\_\_ Not Found
- Renewed
- \_\_\_\_\_ Unrecorded
- \_\_\_\_\_ Surveyed In
- \_\_\_\_\_ Referenced Out

Previous Renewals 32, 50 (REFERENCED OUT FOR LOGGING SECS 60/34)

MONUMENT DETAIL

Monument(s) Found: (Condition and Source)

NONE. CONSTRUCTION OF A LOG LANDING DIRECTLY ABOVE CORNER HAS DESTROYED EVIDENCE AT CORNER POSITION

NONE

Accessories Found:

1- ORIGINAL 3/4 INCH D. FIR NOW A CHARRED STUMP BEARS N 10° W 28.4 FEET (WE DO NOT OPEN BLAZE FOR SCRIBING).

2- FROM RENEWAL NO. 50

2- A BRIDGE SPIKE SET IN ROCK STAMPED "302" BEARS S 57 1/4° W 172.08 FEET (REC. 172.10 FT.)

3- A 5/8" DIA. IRON ROD WITH ALUMINIUM CAP STAMPED "B01" BEARS S 60° E 102.42 (LEVEL CHAINED 92.32 FEET SLOPE CHAINED 11.21 FEET @ AT 42° SLOPE) RECORDED INFORMATION INDICATES A DISTANCE OF 102.08 FEET FOR THIS LINE. A REVIEW OF THE FIELD NOTES FOR RENEWAL NO. 50 INDICATES MEASUREMENTS ON STEEP SLOPES, I ~~WANT TO BE THE~~ ASSUME THIS THE MOST PROBABLE LINE FOR ERROR.

4- RPK NAIL SET IN 30 INCH DIA STUMP BEARING S 60° E 538.87 FEET NOT USED AS FOG HAS VISIBILITY BLOCKED

25-T21-10 ✓  
#27-T21-9 ✓

G.S. No. 61/30-11 C

