

OREGON CORNER RESTORATION FORM

FILED
RECEIVED

AUG 28 1984

Section 20 Township 32S Range 3W
County DOUGLAS Date 7-31-84

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Corner Designation

80 1/16 CORNER OF SECTIONS 20
AND 21, T32S, R3W, WILLAMETTE
MERIDIAN.

Condition Report Only
 Not Found
 Renewed
 Unrecorded
 Surveyed In
 Referenced Out

Previous Renewals/Surveys, etc.

C.S. 30/41A ; M56-20 ; M82-68

Monument(s) & Accessories Found: (Condition and Source)

2" d. I.P. FIRMLY SET, PROJECTING 2" ABOVE A 2' d. MOUND OF
STONE, WITH BRASS CAP MARKED AS SHOWN BELOW, SET BY GLEN
BAUGHMAN, L.S. 536, IN 1975. A 3/4" d. I.P. IS SET ALONGSIDE
(GEORGE WENDEROTH, L.S. 5, IN 1945).

BT BY WENDEROTH IN 1945: AN 8" YEW, N16 1/2° W, 41 1/2 FT., WITH
FRAGMENTARY SCRIBE MARKS VISIBLE ON PARTIALLY HEALED BLAZE
AND BT BY BAUGHMAN IN 1975: A 6" W. FIR SNAG, N01° E, 10 3/4 FT.,
WITH SCRIBE MARKS "1/16 S21 80 BT" VISIBLE ON PARTIALLY HEALED

Monument Detail DOUBLE BLAZE WITH A BRASS WASHER, STAMPED "LS 536";
NAILED TO LOWER BLAZE. SKETCH



A 6 FT. STEEL FENCE POST SET 3 FT. SOUTH WITH
USFS SIGNS #54-2 & -9 ATTACHED.

A 6 FT. CARSONITE POST SET 4 FT. WEST WITH
USFS SIGN #54-2 ATTACHED.

Monument Set (Procedures and Description)

NONE

New Accessories

I MARK A NEW BT:

A 10" W. FIR, N16° E, 26 1/2 FT., SCRIBED "1/16 S21 80 BT"
WITH BRASS WASHER STAMPED "L.S. 1181" NAILED TO BASE
OF SINGLE BLAZE.

Location & Comments

CORNER IS APPROXIMATELY 50 FT WEST OF OLD
ROAD AND 25 FT. EAST OF EAST FORK
OF DISMAL CREEK.

Surveyor's Seal

Compass Declination 21° E
Firm/Agency U.S.F.S.

Address 2900 STEWART PKWY
ROSEBURG, OR, 97470

Party Chief LEONARD HERZSTEIN

Notes LEONARD HERZSTEIN

Witness RANDY LOPEZ



C.S. File No. 62/15-5 C