

FILED  
RECEIVED

NOV 15 1984

OREGON CORNER RESTORATION FORM

Section 2 Township 31S Range 2W

County DOUGLAS Date OCT. 31, 1984

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

Corner Designation

C-N-NW ONE SIXTY-FOURTH ( $\frac{1}{64}$ )  Condition Report Only  
 CORNER OF SECTION TWO (2), TOWNSHIP  Not Found  
 THIRTY-ONE (31) SOUTH, RANGE  Renewed  
 TWO (2) WEST, WILLAMETTE MERIDIAN  Unrecorded  
 Surveyed In  
 Referenced Out

Previous Renewals/Surveys, etc. M 65-68

Monument(s) & Accessories Found: (Condition and Source)

2 3/4" O.D. IRON PIPE, FIRMLY SET, PROJECTING 4" ABOVE GROUND WITH A 3" BRASS CAP MARKED AS SHOWN BELOW, SET BY GLEN BAUGHMAN, L.S. 536, IN 1978.

RND B.T.S MARKED BY BAUGHMAN IN 1978 ?

A 10" D. FIR, N 23° E, 55' FT., WITH FRAGMENTARY SCRIBE MARKS VISIBLE ON PARTIALLY HEALED DOUBLE BLAZE.

A 10" D. FIR BOOT CROWN, S 62° E (REC. S 72° E), 40' FT. WITH 10" LOG ALONGSIDE WITH FRAGMENTARY SCRIBE MARKS VISIBLE

Monument Detail ON PARTIALLY HEALED DOUBLE BLAZE. ~~Sketch~~



A STEEL FENCE POST WAS SET NORTH 3 FT. WITH USFS SIGNS # 54-2 & 54-9 ATTACHED.

Monument Set (Procedures and Description)

NONE

New Accessories

MARKED A NEW BT ?  
A 6" D. FIR, N 65 3/4° W, 62' FT., SCRIBED "C N NW 1/64 S2 BT" ON A DOUBLE BLAZE, WITH A BRASS WASHER STAMPED "LS 1181" NAILED FLUSH TO LOWER BLAZE.

Location & Comments

CORNER IS APPROXIMATELY 250 FT, N 45° E FROM THE END OF USFS ROAD # 1610-051

Compass Declination 18 1/2° E

Firm/Agency U.S. FOREST SERVICE

Address 2900 STEWART PKWY

ROSEBURG, OR, 97470

Party Chief L. HERZSTEIN

Notes LEONARD HERZSTEIN

Witness RANDY LOPEZ

Surveyor's Seal

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Maurice E. Farr*  
OREGON  
SEPT. 23, 1977  
MAURICE E. FARR  
1181

11-13-84