

GOVERNMENT CORNER RESTORATION FORM

FILED

JAN 11 1988

Township 22S Range 13W Sec. 13 County DOUGLAS

State OR Date 1/5/88 No. _____

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE

Corner Designation

CN 1/16

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

MONUMENT DETAIL

Previous Renewals M 1-74, M 66-64

Monument(s) Found: (Condition and Source)

6" X 6" CONCRETE POST WITH TOP LEANING
APPROX. 5" SOUTHERLY OF PLUMB. POST
PROTRUDES 3 FT ABOVE GROUND.
MARKED U.S. ON EAST SIDE. POSSIBLY

A 1/4" I.D. I.P. PROTRUDING 1.5 FT ABOVE
GROUND INSIDE A 2" I.D. I.P. PROTRUDING
1.0 FT ABOVE GROUND (SOURCE UNKNOWN)
LEANING NORTHERLY 4 IN.
(NOTED AS ACCESSORY BELOW)

N/A

SET BY LIGHTHOUSE SERVICE, SEE DEPART-
MENT OF COMMERCE, LIGHTHOUSE SERVICE
LETTER BETWEEN R. R. TINKHAM (SUPER-
INTENDENT OF LIGHTHOUSES) AND H. L.
EPPSTEIN (COUNTY SURVEYOR) IN C.S. FILE #18/20A
DATED AUGUST 22, 1931.

Accessories Found:

BEARINGS AND DIST. TAKEN TO PLUMB POSITION OF CONCRETE POST
30" NOW 36" DIA. 8 FT HIGH BROKEN AND ROTTEN SPRUCE STUMP,
SCRIBING FOUND "GS 1/16" BEARS N71°W, 3.2 FT. (RECORD
WEST, 2.3 FT) PER M 1-74

30" DIA. SPRUCE NOW DOWN AND TIPPED OUT OF POSITION, ROOT WAS
IS NEAR RECORD BEARING AND DISTANCE (S54°E, 16.0 FT) PER M 66-64

A 1/4" I.D. I.P. PROTRUDING 1.5 FT ABOVE GROUND INSIDE A 2" I.D.
I.P. PROTRUDING 1.0 FT ABOVE GROUND, BEARS S5°E, 4.8 FT (MEAS. BETWEEN
APPROX PLUMB POSITION OF CONCRETE POST AND I.P.'S). (REC. S5°E,
3.8 FT DISTANCE TO TOP OF I.P.'S AND CONC. POST PER M 66-64).
SOURCE UNKNOWN

STEEL POST AND RAOULE "OREGON STATE PARK BOUNDARY"
BEARS S8°E, 2.4 FT (RECORD) SOUTH, 2 FT. PER M 66-64)

31" NOW 37" DIA SPRUCE WITH A PARTIALLY HEALED SINGLE BLAZE
AND INLEGIBLE SCRIBE VISIBLE. WE OPEN AND FIND "CN 1/16 S13 BT"
SCRIBED IN BLAZE. BEARS N27°E, 21.6 FT REC. (N9°E, 20.2 FT)
PER M 66-64

#284

640460

C.S. File No. 62/49-5

