



**FILED**

DEC 4 1989

TF  
COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

TF

BEARINGS BASED ON  
SOLAR OBSERVATION.

# PLAT

SHOWING A SURVEY IN SECTION 26, T.32S.,  
R.4W., W.M., DOUGLAS COUNTY, OREGON.

**COUNTY SURVEYORS FILE DATA  
DO NOT REMOVE FROM OFFICE**

## LEGEND

○ SET 5/8" X 30" IRON ROD WITH YELLOW PLASTIC  
CAP MARKED "NYGREN LS1035".

⊙ FOUND BRASS CAP & BEARING TREES.

NOTE: SURVEY NARRATIVE IS SEPERATE DOCUMENT.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Gerald V. Nygren*

OREGON  
GERALD V. NYGREN  
AUGUST 22, 1975  
1035

SURVEYED FOR:  
BOISE CASCADE CORP.  
P.O. BOX 100  
MEDFORD, OREGON 97501

GERALD V. NYGREN  
522 BARKER DRIVE  
MERLIN, OREGON 97532

DATE: NOV. 2, 1989.  
SCALE: 1" = 1000'  
JOB NO. 89-41

FILED

*JK*

DEC 4 1989 TF

SURVEY NARRATIVE to comply with O.R.S. 209.250

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

TF

DATE: November 2, 1989.

SURVEYED FOR: Boise Cascade Corp.  
P.O. Box 100  
Medford, Oregon 97501

SURVEYED BY: Gerald V. Nygren  
522 Barker Drive  
Merlin, Oregon 97532

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Gerald V. Nygren*

OREGON  
GERALD V. NYGREN  
AUGUST 22, 1975  
1035

LOCATION: Section 26, Township 32 South, Range 4 West,  
Willamette Meridian, Douglas County, Oregon.

PURPOSE: To survey and mark the North-South centerline  
of said Section 26.

PROCEDURE: After a diligent search I was unable to find the  
North Quarter corner of said Section 26. I traversed  
from the Northwest corner of said Section 26 to the  
Northeast corner of said Section 26 and found the  
distance to be over 400 feet longer then the original  
G.L.O. record distance. I made another diligent  
search 200 feet West and 200 feet East of the Mid-point  
with no success. The search area has been devastated  
by logging that appears to be 30 to 40 years old.  
I set the North Quarter corner of said Section 26  
by single proportion which I monumented with a 5/8"  
X 30" iron rod and scribe the folowing bearing trees:

- A 3" dia. D. Fir, N80 W, 25.3 Ft. scribed "X BT"
- A 8" dia. D. Fir, N58 W, 26.3 Ft. scribed "1/4 S23 BT
- A 8" dia. D. Fir, S22 E, 16.5 Ft. scribed "1/4 S26 BT
- A 14" dia. D. Fir, N26 E, 5.2 Ft. scribed "1/4 S23 BT

thence I traversed South 0 42'38" West, 5312.34 feet  
to the South Quarter corner of said Section 26.

Bearing are based on solar observation.

A Wild T-16 theodolite and MAC-1E EDM were used  
to execute this survey.