

TOWNSHIP 32 SOUTH
RANGE 3 WEST

FILED

zh

NOV 9 1988

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE

FIRST RE-ESTABLISHMENT

Section corner common to Sections 25, 26, 35 and 36, Township 32 South, Range 3 West, W.M.

Fd. projecting 12 ins. (leaning 25° southeast of vertical) the 1½ ins. diam. galvanized iron pipe, with 3 ins. diam. brass cap, mkd.:

OREGON STATE BOARD OF FORESTRY

T32SR3W

S26 | S25

S35 | S36

1968

RS359

set on Survey No. 3967, dated 1969.

Said brass cap is centered over a chiseled cross atop the (firmly set) 10x7x7 ins. original stone, fd. projecting 6 ins. Original bearing trees recorded by F.Mensch in 1913 fd. as follows:

Burnt fir stump, 48 ins. diam., brs. N55°46'E, 35.64 ft. to center. Record; N55°E.

Burnt fir stump, 45 ins. diam., brs. S16°41'E, 7.50 ft. to center. Record; S15°E, 6.60 ft.

Burnt fir stump, 51 ins. diam., brs. S35°05'W, 18.80 ft. to center. Record; S35°W, 17.82 ft.

Burnt fir stump, 66 ins. diam., brs. N44°57'W, 39.45 ft. to center. Record; N44°W, 37.62 ft.

A bearing tree mkd. on the above noted survey, a cedar, now a burnt snag, 32 ins. diam., brs. S5°49'E, 31.5 ft. Record; S8½°E, 31.6 ft.

The above bearing trees were also reported by the Douglas County Surveyor's office on 1969 re-establishment; reference Survey No. 4185. Bearing trees mkd. by the county surveyor fd:

Burnt pine stump, 16 ins. diam., brs. N21°E, 31.3 ft. to center. Record; 31.5 ft.

Burnt fir snag, 7 ins. diam. with healed blazes, brs. S41°E, 15.90 ft. to center. Record; 16.2 ft.

Burnt fir stump, 21 ins. diam., brs. S69°39'W, 39.75 ft. to center. Record; S70°W, 40.2 ft.

A bearing tree, not of record (in Jackson County), a burnt fir snag, 7 ins. diam., with nail through washer, stamped "CS 536" in lower, burned face, brs. N28°43'E, 10.45 ft.

As all trees within a reasonable distance of the corner have been destroyed by recent (1987) forest fire, set new references; 5/8x24 ins. rebars with yellow plastic caps mkd. "Jackson C.S.", 23 ins. in the ground, except as noted:

1. N41°59'E, 12.15 ft.
2. S38°00'E, 9.05 ft.
3. S73°24'W, 122.45 ft., set 3 ins. deep, 3 ft. South of metal fence post, with attached attention sign, located alongside road, c. N45°E-S45°W.
4. N37°23'W, 9.57 ft.

Corner lies on Southeast slope, an estimated 160 ft. West of draw c. Southeast and 3 ft. West of steel fence post with attention sign.

November 1, 1988

R.Frost, Tech.

H.Durkee, Tech.

Edward McGinty

County Surveyor

p-363-365

#231 x

C.S. File No. 63/82-2 c