

TOWNSHIP 32 SOUTH

RANGE 3 WEST

FILED

NOV 9 1988

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE

FIRST RE-ESTABLISHMENT

Section corner common to Sections 26, 27, 34 and 35, Township 32 South, Range 3 West, W.M.

Fd. projecting 12 ins., the 1 ins. diam. galvanized iron pipe, with 2 1/2 ins. diam. brass cap mkd.:

COUNTY SURVEYORS OFFICE

T32S R3W

DOUG. CO.

S27 | S26

S34 | S35

JACK. CO.

1969

set by the Douglas County Surveyor per Survey No. 4185, dated 1969.

The original stone, mkd. with cross on top, recorded by F.Mensch, in 1913, is found deposited (buried) alongside corner.

Original bearing trees fd. as follows:

Sawed fir stump, 25 ins. diam., containing scribe mks. brs. N18°E, 5.45 ft. to center. Record; N14°E, 4.62 ft.

The center of rotted fir stump, 20 ins. diam., brs. record; S60°E, 17.16 ft.

The middle of rotted fir stump remains, brs. record; S45°W, 10.56 ft.

Rotted fir stump, 24 ins. diam., containing reverse impression of scribe mks. including "BT", brs. N40°30'W, 8.2 ft. to center. Record; N48°W, 7.26 ft.

Bearing trees mkd. by Douglas County in 1969 fd. and measured to center of trees near base:

Hemlock, 12 ins. diam., with scribe mks. visible in partially healed blaze, brs. N69°E, 6.4 ft. Record; 5.9 ft.

Hemlock, 10 ins. diam., containing scribe mks. in partly exposed face, brs. S66°E, 4.60 ft. Record; 4.40 ft.

Hemlock, 11 ins. diam., with healed blaze, brs. S18°W, 18.3 ft. Record; 19.0 ft.

The Northwest bearing tree is now gone. As there is no suitable tree in Section 27, set a 5/8x24 ins. rebar, 23 ins. in the ground with yellow plastic cap, mkd. "Jackson C.S.", located 6 ft. South of a 28 ins. diam. fir stump, brs. N1°18'W, 48.59 ft.

Corner lies at top of cut-bank, 8 ft. above and 30 ft. South of middle of road, C. S50°W and about 6 ft. South of location marker on original Northeast B.T. (stump) alongside road.

October 20, 1988
R.Frost, Tech.
S.Beecher, Tech.

Edward McGinty
County Surveyor

p-359

2294

C.S. File No. 63/82-4c